
Proposed Subdivision
Billy's Lookout - Stage 7
Site Classification

Fishermans Drive, Teralba

NEW15P-0070A-AK
27 March 2018



27 March 2018

McCloy Development Management Pty Ltd
Suite 1, Level 3, 426 King Street
NEWCASTLE WEST NSW 2309

Attention: Jon Hines

Dear Sir,

**RE: PROPOSED SUBDIVISION – BILLY'S LOOKOUT – STAGE 7
FISHERMANS DRIVE, TERALBA
SITE CLASSIFICATION (LOTS 701 TO 730)**

Please find enclosed our geotechnical report for Stage 7 of the residential subdivision of Billy's Lookout, located at Fishermans Drive, Teralba.

The report provides site classification with respect to reactive soils, in accordance with the requirements of AS2870-2011 '*Residential Slabs and Footings*', Stage 7 (Lots 701 to 730).

If you have any questions regarding this report, please do not hesitate to contact Shannon Kelly or the undersigned.

For and on behalf of Qualtest Laboratory (NSW) Pty Ltd

A handwritten signature in black ink, appearing to read 'Jason Lee', written in a cursive style.

Jason Lee
Principal Geotechnical Engineer

Table of Contents:

1.0	Introduction	1
2.0	Desktop Study	1
3.0	Field Work	1
4.0	Site Description	2
4.1	Site Regrade Works.....	2
4.2	Surface Conditions	2
4.3	Subsurface Conditions.....	3
5.0	Laboratory Testing	7
6.0	Site Classification to AS2870-2011	8
7.0	Limitations.....	9

Attachments:

Figure AK1:	Approximate Test Location Plan
Appendix A:	Engineering Logs of Test Pits
Appendix B:	Results of Laboratory Testing
Appendix C:	CSIRO Sheet BTF 18 - Foundation Maintenance and Footing Performance

1.0 Introduction

Qualtest Laboratory NSW Pty Ltd (Qualtest) is pleased to present this site classification report on behalf of McCloy Development Management Pty Ltd (McCloy), for Stage 7 of the residential subdivision of Billy's Lookout, located at Fishermans Drive, Teralba.

Based on the brief and drawing provided by the client, Stage 7 is understood to comprise of 30 residential allotments (Lots 701 to 730).

The scope of work for the geotechnical investigation included providing site classification with respect to reactive soils, in accordance with the requirements of AS2870-2011 '*Residential Slabs and Footings*', for Stage 7 following completion of site regrade works.

This report presents the results of the field work investigations and laboratory testing, and provides recommendations for the scope outlined above.

2.0 Desktop Study

The scope of work has included a review of the following reports completed by Qualtest:

- Site Classification report, 'Proposed Subdivision, Billy's Lookout – Stage 7, Fishermans Drive, Teralba, (Report Reference: NEW15P-0070A-AI, dated 6 September 2017);
- Site Classification report, 'Proposed Subdivision, Billy's Lookout – Stages 5 to 9, Fishermans Drive, Teralba, (Report Reference: NEW15P-0070A-AA, dated 16 February 2016);
- Site Classification report, 'Proposed Subdivision, Billy's Lookout – Stage 5, Fishermans Drive, Teralba, (Report Reference: NEW15P-0070A-AB, dated 16 June 2016);
- Site Classification report, 'Proposed Subdivision, Billy's Lookout – Stage 5, Fishermans Drive, Teralba, (Report Reference: NEW15P-0070A-AH, dated 11 August 2017);
- Site Classification report, 'Proposed Subdivision, Billy's Lookout – Stages 6 & 9, Fishermans Drive, Teralba, (Report Reference: NEW15P-0070A-AJ, dated 15 November 2017);

This report includes a summary of selected results from the previous reports where applicable.

3.0 Field Work

Following site regrade works, additional field work investigations were carried out on 6 March 2018, comprising of:

- Excavation of fourteen test pits (TP701 to TP714) using a 5 tonne tracked excavator with a 0.30m wide toothed bucket, to depths of between 0.21m – 2.00m;
- Small disturbed samples were taken for subsequent laboratory testing;
- Test pits were backfilled with the excavation spoil and compacted using the excavator bucket and tracks.

Investigations were carried out by an experienced Geotechnical Engineer from Qualtest who located the test pits, carried out the testing and sampling, produced field logs of the test pits, and made observations of the site surface conditions.

Approximate test pit locations are shown on the attached Figure AK1, which also includes test pit locations from the previous investigations conducted on site. Engineering logs of the test pits are presented in Appendix A. Density estimates for granular materials shown on the logs were assessed based upon visual and tactile observations only.

4.0 Site Description

4.1 Site Regrade Works

Site re-grading works were conducted on Lots 701 to 730 within Stage 7. It is understood that for the majority of lots, site re-grade works were limited to cutting to varying depths, and typically placement of fill (mostly topsoil) to depths of less than or equal to 0.4m.

Lots 702, 703, 706 and 707 have been filled using approved site won material. Prior to filling, lot re-grade areas were stripped of all topsoil and unsuitable material to expose suitable natural residual foundation profile. Re-grade works then consisted of filling with approved site fill to finish design levels.

Filling was performed using site material won from excavations cut from around the site. The fill material could generally be described as mixtures of Sandy Gravelly CLAY, and Sandy CLAY, of medium plasticity, with fine to coarse grained sand and gravel (from weathered rock).

As the geotechnical testing authority engaged for the project, we state that the filling performed for the regrade areas (Lots 702, 703, 706 and 707), was carried out to Level 1 criteria as defined in Clause 8.2 – Section 8, of AS3798-2007, 'Guidelines on Earthworks for Commercial and Residential Developments'.

Reference should be made to 'Level 1 Site Re-grade Assessment Report' (Qualtest Ref: NEW17P-0199-AA) for details of the site regrade works conducted by Qualtest.

The recommendations of this report are based on the understanding that any existing lot re-grade works outside the areas described above are limited to cutting and/or placement of fill such that total fill and topsoil depths do not exceed 0.4m. Qualtest should be informed without delay if additional earthworks are known to have been carried out.

4.2 Surface Conditions

Selected photographs of the site are shown below.



Photograph 1: Facing south from near northern corner of Lot 705, Excavator at TP702.



Photograph 2: Facing southwest from near northern corner of Lot 705.



Photograph 3: Facing east from near TP706, Wheelhouse Road visible in background.



Photograph 4: Facing southeast from near TP706 (from Lot 729).



Photograph 5: Facing east from Lot 706.



Photograph 6: Facing southeast from Lot 706.

4.3 Subsurface Conditions

Reference to the 1:100,000 Newcastle Coalfield Regional Geology Sheet indicates the site to be underlain by the Clifton Subgroup of the Narrabeen Group, and the Moon Island Beach Subgroup of the Newcastle Coal Measures, which are characterised by Conglomerate, Sandstone, Siltstone, Claystone, Tuff and Coal rock types.

Table 1 presents a summary of the typical soil types encountered on site during the field investigations, divided into representative geotechnical units.

Table 2 contains a summary of the distribution of the above geotechnical units at the test pit locations.

No groundwater levels or water inflows were encountered in the test pits during the limited time that they remained open on the day of the field investigation.

It should be noted that groundwater conditions can vary due to rainfall and other influences including regional groundwater flow, temperature, permeability, recharge areas, surface condition, and subsoil drainage.

Reference should be made to the previous reports outlined in Section 2.0 for further details of site description, subsurface conditions, field work conducted, engineering logs of test pits, laboratory testing results, site supervision and density testing carried out as part of those previous assessments.

TABLE 1 – SUMMARY OF GEOTECHNICAL UNITS AND SOIL TYPES

Unit	Soil Type	Description
1A	FILL – TOPSOIL & MULCH	Generally up to about 50mm of mulch, overlying Sandy CLAY / Clayey SAND – low to medium plasticity, fine to coarse grained, dark grey to grey, low to medium plasticity, with some fine to medium grained gravel in places, root affected in places.
1B	FILL	Sandy CLAY – medium and low to medium plasticity, dark grey-brown, orange-brown to dark orange and pale grey-white, fine to coarse grained sand, with some fine to medium grained sub-angular to sub-rounded gravel and trace cobbles in places. SAND – fine to coarse grained, grey. Clayey SAND – fine to coarse grained, grey to grey-brown, fines of low to medium plasticity, trace fine to medium grained sub-rounded to sub-angular gravel.
2	TOPSOIL	Silty SAND - fine to coarse grained, grey, fines of low plasticity, root affected. Clayey SAND - fine to coarse grained, dark brown to grey, fines of medium plasticity, root affected.
3	SLOPEWASH / COLLUVIUM	Silty SAND, SAND - fine to medium grained, pale brown / grey, some Silt / fines of low plasticity. Clayey SAND - fine to coarse grained, dark brown to grey, fines of medium plasticity.
4	RESIDUAL SOIL	Silty CLAY / Sandy CLAY – medium and medium to high plasticity, variable colours such as pale brown, orange to pale brown, pale grey, grey, and brown to red, some sand / fine to coarse grained sand. Clayey SAND / SAND – fine to coarse grained, orange-brown and pale grey-white, with clay / fines of low to medium plasticity, trace fine to medium grained sub-angular to sub-rounded gravel.
5	EXTREMELY WEATHERED (XW) ROCK	Extremely Weathered Sandy SILTSTONE / SANDSTONE with Soil Properties; excavating as SAND – fine to coarse grained, pale grey-white and orange-brown to orange, with some clay. Breaks down into Clayey SAND in places.
6	HIGHLY WEATHERED (HW) ROCK	SANDSTONE - fine to coarse grained, variable colours such as pale grey to white, grey, orange, pale brown, variable estimated strength ranging from low to high. Sandy SILTSTONE – pale orange-brown to brown and pale grey, estimated medium strength, with some Extremely Weathered pockets.

TABLE 2 – SUMMARY OF GEOTECHNICAL UNITS ENCOUNTERED AT TEST PIT LOCATIONS

TEST PIT NO.	UNIT 1A Fill – Mulch & Topsoil	UNIT 1B Fill	UNIT 2 Topsoil	Unit 3 Slopewash / Colluvium	Unit 4 Residual Soil	Unit 5 XW Rock	Unit 6 HW Rock
	Depth (m)						
Current Geotechnical Assessment (Ref: NEW15P-0070A-AK, March 2018)							
TP701	0.00 - 0.25	-	-	-	0.25 - 2.00	-	-
TP702	0.00 - 0.25	-	-	0.25 - 0.40	0.40 - 0.70	-	0.70 - 0.71*
TP703	0.00 - 0.20	0.20 - 0.40	-	-	-	-	0.40 - 0.41*
TP704	0.00 - 0.18	-	-	-	0.18 - 0.80	-	0.80 - 0.81*
TP705	0.00 - 0.20	-	-	-	-	-	0.20 - 0.21*
TP706	0.00 - 0.25	-	-	-	0.25 - 0.60	-	0.60 - 0.61*
TP707	0.00 - 0.35	-	-	-	-	0.35 - 0.75	0.75 - 0.77*
TP708	0.00 - 0.20	-	-	-	0.20 - 0.25	0.25 - 0.65	0.65 - 0.66*
TP709	0.00 - 0.20	-	-	-	-	0.20 - 0.30	0.30 - 0.33*
TP710	-	-	-	-	-	0.00 - 0.25	0.25 - 0.28*
TP711	0.00 - 0.38	-	-	-	-	0.38 - 1.30	1.30 - 1.35*
TP712	0.00 - 0.06	0.06 - 0.25	-	-	0.25 - 1.00	-	1.00 - 1.15*
TP713	0.00 - 0.25	-	-	-	-	-	0.25 - 0.30*
TP714	0.00 - 0.25	-	-	-	-	0.25 - 1.40^	-
Previous Geotechnical Assessment (Ref: NEW15P-0070A-AJ, November 2017)							
TP601	-	-	0.00 - 0.25	-	-	-	0.25 - 0.35*
TP602	0.00 - 0.20	-	-	-	0.20 - 0.25	-	0.25 - 0.27*

TEST PIT NO.	UNIT 1A Fill – Mulch & Topsoil	UNIT 1B Fill	UNIT 2 Topsoil	Unit 3 Slopewash / Colluvium	Unit 4 Residual Soil	Unit 5 XW Rock	Unit 6 HW Rock
	Depth (m)						
TP903	0.00 - 0.20	-	-	-	-	-	0.20 - 0.25*
Previous Geotechnical Assessment (Ref: NEW15P-0070A-AH, August 2017)							
TP5-3	0.00 - 0.20	0.20 - 0.95	-	-	0.95 - 1.50	-	-
TP5-5	0.00 - 0.25	0.25 - 1.20	-	-	1.20 - 1.40	-	-
Previous Geotechnical Assessment (Ref: NEW15P-0070A-AB, June 2016)							
TP204	-	-	0.00 - 0.18	0.18 - 0.27	0.27 - 0.40	-	0.40 - 0.65#
Previous Geotechnical Assessment (Ref: NEW15P-0070A-AA, February 2016)							
TP105	-	-	0.00 - 0.25	-	0.25 - 1.00	-	1.00 - 2.30^
TP107	-	-	0.00 - 0.20	-	0.20 - 0.50	-	0.50 - 0.75*
TP108	-	-	0.00 - 0.20	-	0.20 - 0.70	-	0.70 - 0.80*
TP111	-	-	0.00 - 0.15	-	0.15 - 0.45	-	0.45 - 0.50*
TP112	-	-	0.00 - 0.25	-	0.25 - 0.80	-	0.80 - 0.90*
Notes: <ul style="list-style-type: none"> * = Practical refusal or refusal of 5 tonne excavator met on Highly Weathered Rock. # = Practical refusal or refusal of 22 tonne excavator met on Highly Weathered Rock (preliminary investigation Feb 2016). ^ = Slow to very slow progress, close to practical excavator refusal. 							

5.0 Laboratory Testing

Samples collected during the field investigations were returned to our NATA accredited Warabrook Laboratory for testing which comprised of:

- (12 no.) Atterberg Limits tests.

Results of the laboratory testing are presented in Appendix B, with a summary of the Atterberg Limits test results presented in Table 3.

Table 3 and Table 4 also include a summary of laboratory testing information (where applicable) from the previous Geotechnical Assessment works carried out by Qualtest.

TABLE 3 – SUMMARY OF ATTERBERG LIMITS TESTING RESULTS

Location	Depth (m)	Material Description	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (%)	Linear Shrinkage (%)
Current Investigation (March 2018)						
TP701	0.80 – 1.00	(CH) Silty CLAY	52	17	35	9.0
TP702	0.40 – 0.60	(SC) Clayey SAND	39	18	21	7.0
TP703	0.05 – 0.20	FILL: TOPSOIL (CL) Sandy CLAY	24	16	8	3.5
TP704	0.20 – 0.40	(SC) Gravelly Clayey SAND	26	17	9	4.0
TP705	0.10 – 0.20	FILL: TOPSOIL (CL) Sandy CLAY	24	18	6	3.0
TP706	0.30 – 0.50	(SC) Clayey SAND	27	17	10	3.5
TP707	0.60 – 0.70	(EW) Extremely Weathered Sandstone with soil properties	30	15	15	5.0
TP708	0.30 – 0.50	(EW) Extremely Weathered Sandstone with soil properties	26	16	10	4.0
TP711	0.10 – 0.20	FILL: TOPSOIL (SC) Clayey SAND	26	19	7	3.0
TP711	0.40 – 0.60	(EW) Extremely Weathered Sandstone with soil properties	36	16	20	7.0
TP712	0.30 – 0.50	(CH) Sandy CLAY	52	21	31	9.0

Location	Depth (m)	Material Description	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (%)	Linear Shrinkage (%)
TP714	0.30 – 0.50	(EW) Extremely Weathered Sandy Siltstone with soil properties	43	20	23	7.0
Previous Investigation (June 2016 & November 2017)						
TP204	0.30 – 0.40	(CH) Sandy CLAY	68	19	49	16.0
TP602	0.20 – 0.25	(SC) Clayey SAND	27	17	10	3.5
TP903	0.10 – 0.20	FILL: (SC) Clayey	23	15	8	3.0

Table 4 presents a summary of shrink/swell test results from the previous Geotechnical Assessment works carried out by Qualtest.

TABLE 4 – SUMMARY OF SHRINK / SWELL TESTING RESULTS

Location	Depth (m)	Material Description	I _{ss} (%)
Previous Investigations (February 2016 & August 2017)			
TP5-5	0.40 – 0.80	FILL: (CH) Sandy CLAY	0.9
TP105	0.40 – 0.80	(CH) CLAY	1.3
TP112	0.30 – 0.55	(CH) Sandy CLAY	1.1

6.0 Site Classification to AS2870-2011

Based on the results of the field work, laboratory testing, and Level 1 site supervision and testing carried out, residential lots located within Stage 7 of the Billy's Lookout subdivision located Fishermans Drive, Teralba, as shown on Figure AK1, are classified in their current condition in accordance with AS2870-2011 'Residential Slabs and Footings', as shown in Table 5.

TABLE 5 – SITE CLASSIFICATION TO AS2870-2011

Stage	Lot Numbers	Site Classification	Estimated Characteristic Free Surface Movement
7	Lots 701 to 730	M	20mm to 40mm

Characteristic free surface movements have been estimated for lots in their existing condition as shown in Table 5.

The effects of changes to the soil profile by additional cutting and filling and the effects of past and future trees should be considered in selection of the design value for differential movement.

If site re-grading works involving cutting or filling are performed after the date of this assessment the classification may change and further advice should be sought.

Final site classification will be dependent on the type of fill and level of supervision carried out. Re-classification of lots should be confirmed by the geotechnical authority at the time of construction following any site re-grade works.

Footings for the proposed development should be designed and constructed in accordance with the requirements of AS2870-2011.

The classification presented above assumes that:

- All footings are founded in controlled fill (if applicable) or in the residual clayey soils or rock below all non-controlled fill, topsoil material and root zones, and fill under slab panels meets the requirements of AS2870-2011, in particular, the root zone must be removed prior to the placement of fill materials beneath slabs.
- The performance expectations set out in Appendix B of AS2870-2011 are acceptable, and that site foundation maintenance is undertaken to avoid extremes of wetting and drying.
- Footings are to be founded outside of or below all zones of influence resulting from existing or future service trenches.
- The constructional and architectural requirements for reactive clay sites set out in AS2870-2011 are followed.
- Adherence to the detailing requirement outlined in Section 5 of AS2870-2011 '*Residential Slabs and Footings*' is essential, in particular Section 5.6, '*Additional requirements for Classes M, H1, H2 and E sites*' including architectural restrictions, plumbing and drainage requirements.
- Site maintenance complies with the provisions of CSIRO Sheet BTF 18, "*Foundation Maintenance and Footing Performance: A Homeowner's Guide*", a copy of which is attached in Appendix C.

All structural elements on all lots regardless of their site classification should be supported on footings founded beneath all uncontrolled fill, layers of inadequate bearing capacity, soft/loose, or other potentially deleterious material.

If any areas of uncontrolled fill of depths greater than 0.4m are encountered during construction, footings should be designed in accordance with engineering principles for Class 'P' sites.

7.0 Limitations

The findings presented in the report and used as the basis for recommendations presented herein were obtained using normal, industry accepted geotechnical design practices and standards. To our knowledge, they represent a reasonable interpretation of the general conditions of the site.

The extent of testing associated with this assessment is limited to discrete test pit locations. It should be noted that subsurface conditions between and away from the test pit locations may be different to those observed during the field work and used as the basis of the recommendations contained in this report.

If subsurface conditions encountered during construction differ from those given in this report, further advice should be sought without delay.

Data and opinions contained within the report may not be used in other contexts or for any other purposes without prior review and agreement by Qualtest. If this report is reproduced, it must be in full.

If you have any further questions regarding this report, please do not hesitate to contact Shannon Kelly or the undersigned.

For and on behalf of Qualtest Laboratory (NSW) Pty Ltd.

A handwritten signature in black ink, appearing to read 'Jason Lee', with a stylized, cursive script.

Jason Lee
Principal Geotechnical Engineer

FIGURES:

Figure AK1 –Approximate Test Pit Location Plan




LEGEND:



Approximate test pit location.
(Qualtest, March 2018)



Approximate test pit location.
(Qualtest, Previous Investigations)



Based on sale plan provided by client.



Client:	MCCLOY GROUP	Drawing No:	FIGURE AK1
Project:	PROPOSED SUBDIVISION - BILLY'S LOOKOUT - STAGE 7	Project No:	NEW15P-0070A
Location:	FISHERMANS DRIVE, TERALBA	Scale:	N.T.S.
Title:	APPROXIMATE TEST PIT LOCATION PLAN	Date:	27 MARCH 2018

APPENDIX A:




Engineering Logs of Test Pits

ENGINEERING LOG - TEST PIT

CLIENT: McCLOY GROUP
PROJECT: PROPOSED SUBDIVISION - STAGE 7
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP701
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 6-3-18

EQUIPMENT TYPE: 5 TONNE EXCAVATOR
TEST PIT LENGTH: 2.0 m **WIDTH:** 0.3 m
SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations	
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result		
E	Not Encountered	D				CL	0.03m FILL: Tree Mulch FILL: TOPSOIL - Sandy CLAY - low to medium plasticity, dark grey to dark brown, fine to coarse sand, trace fine to medium grained sub-angular gravel.	D - M		HP	350	FILL: TREE MULCH FILL: TOPSOIL	
						SC	0.25m Clayey SAND - fine to coarse grained, orange-brown to red-brown and pale grey, with fine to coarse grained sub-angular gravel, trace cobbles.		MD - D			RESIDUAL SOIL	
				0.5		CH	0.60m Silty CLAY - medium to high plasticity, pale grey and pale orange-brown, with bands of extremely to high weathered rock.	M ~ w _p	VSt			HP	380
				1.0			2.00m Hole Terminated at 2.00 m						

LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)		Moisture Condition	
Water		U ₃₀ 50mm Diameter tube sample		VS	Very Soft	<25		D	Dry
Water Level (Date and time shown)		CBR Bulk sample for CBR testing		S	Soft	25 - 50		M	Moist
Water Inflow		E Environmental sample (Glass jar, sealed and chilled on site)		F	Firm	50 - 100		W	Wet
Water Outflow		ASS Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)		St	Stiff	100 - 200		W _p	Plastic Limit
Strata Changes		B Bulk Sample		VSt	Very Stiff	200 - 400		W _L	Liquid Limit
Gradational or transitional strata		Field Tests		H	Hard	>400			
Definitive or distinct strata change		PID Photoionisation detector reading (ppm)		Fb	Friable				
		DCP(x-y) Dynamic penetrometer test (test depth interval shown)		Density	V	Very Loose	Density Index <15%		
		HP Hand Penetrometer test (UCS kPa)			L	Loose	Density Index 15 - 35%		
					MD	Medium Dense	Density Index 35 - 65%		
					D	Dense	Density Index 65 - 85%		
					VD	Very Dense	Density Index 85 - 100%		

ENGINEERING LOG - TEST PIT

CLIENT: McCLOY GROUP

PROJECT: PROPOSED SUBDIVISION - STAGE 7

LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO:

TP702

PAGE:

1 OF 1

JOB NO:

NEW15P-0070A

LOGGED BY:

BE

DATE:


6-3-18

EQUIPMENT TYPE: 5 TONNE EXCAVATOR

SURFACE RL:

TEST PIT LENGTH: 2.0 m WIDTH: 0.3 m

DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations		
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result			
E	Not Encountered	0.10m		0.5		0.03m	FILL: Tree Mulch	M		HP	180 - 250	FILL: TREE MULCH		
		D 0.20m				CL	FILL: TOPSOIL - Sandy CLAY - low to medium plasticity, brown to dark brown with some orange-brown, trace fine to medium grained sub-angular gravel.	M > w _p				FILL: TOPSOIL		
		0.40m				SP	SAND - fine to coarse grained, dark grey, with some fine to medium grained sub-angular gravel, with some clay pockets, medium to high plasticity.					MD	COLLUVIUM / POSSIBLE FILL	
						D 0.60m	SC	Clayey SAND - fine to coarse grained, orange-brown and pale grey, medium plasticity, with sub-angular gravel.				M	MD - D	RESIDUAL SOIL
							0.70m 0.71m	SANDSTONE - fine to coarse grained, pale grey and pale brown, estimated medium to high strength. Hole Terminated at 0.71 m Refusal				D	HIGHLY WEATHERED ROCK	

LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition
Water		U ₅₀	50mm Diameter tube sample	VS	Very Soft	<25	D Dry
Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M Moist
Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W Wet
Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L Liquid Limit
Gradational or transitional strata		Field Tests		H	Hard	>400	
Definitive or distinct strata change		PID	Photoionisation detector reading (ppm)	Fb	Friable		
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	Density	V	Very Loose	Density Index <15%
		HP	Hand Penetrometer test (UCS kPa)	L	Loose		Density Index 15 - 35%
				MD	Medium Dense		Density Index 35 - 65%
				D	Dense		Density Index 65 - 85%
				VD	Very Dense		Density Index 85 - 100%

ENGINEERING LOG - TEST PIT

CLIENT: McCLOY GROUP

PROJECT: PROPOSED SUBDIVISION - STAGE 7

LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO:

TP703

PAGE:

1 OF 1

JOB NO:

NEW15P-0070A

LOGGED BY:

BE

DATE:


6-3-18

EQUIPMENT TYPE: 5 TONNE EXCAVATOR

SURFACE RL:

TEST PIT LENGTH: 2.0 m WIDTH: 0.3 m

DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered	0.05m				CL	0.03m FILL: Tree Mulch	M		HP	180	FILL: TREE MULCH
		D					M > w _p	FILL: Sandy CLAY - low to medium plasticity, brown to dark brown and grey, fine to coarse grained sand.				FILL: TOPSOIL
		0.20m						FILL: Sandy CLAY - medium plasticity, fine to coarse grained, orange-brown and pale grey.				FILL
		D										
		0.40m					0.40m SANDSTONE - fine to coarse grained, pale grey and pale brown, estimated medium to high strength. Hole Terminated at 0.41 m Refusal	D			HIGHLY WEATHERED ROCK	
				0.5								
				1.0								
				1.5								
				2.0								

LEGEND:

Water

- Water Level (Date and time shown)
- Water Inflow
- Water Outflow

Strata Changes

- Gradational or transitional strata
- Definitive or distinct strata change

Notes, Samples and Tests

- U₃₀ 50mm Diameter tube sample
- CBR Bulk sample for CBR testing
- E Environmental sample (Glass jar, sealed and chilled on site)
- ASS Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)
- B Bulk Sample

Field Tests

- PID Photoionisation detector reading (ppm)
- DCP(x-y) Dynamic penetrometer test (test depth interval shown)
- HP Hand Penetrometer test (UCS kPa)

Consistency

- VS Very Soft
- S Soft
- F Firm
- St Stiff
- VSt Very Stiff
- H Hard
- Fb Friable

UCS (kPa)

- <25
- 25 - 50
- 50 - 100
- 100 - 200
- 200 - 400
- >400

Moisture Condition

- D Dry
- M Moist
- W Wet
- W_p Plastic Limit
- W_L Liquid Limit

Density

- V Very Loose
- L Loose
- MD Medium Dense
- D Dense
- VD Very Dense


- Density Index <15%
- Density Index 15 - 35%
- Density Index 35 - 65%
- Density Index 65 - 85%
- Density Index 85 - 100%

ENGINEERING LOG - TEST PIT

CLIENT: McCLOY GROUP
PROJECT: PROPOSED SUBDIVISION - STAGE 7
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP704
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 6-3-18

EQUIPMENT TYPE: 5 TONNE EXCAVATOR
TEST PIT LENGTH: 2.0 m **WIDTH:** 0.3 m
SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations	
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result		
E	Not Encountered	0.05m		0.5		CL	0.04m FILL: Tree Mulch	M		HP	220	FILL: TREE MULCH	
		FILL: TOPSOIL - Sandy CLAY - low to medium plasticity, dark grey to dark brown, fine to coarse grained sand, trace fine to medium grained sub-angular gravel.					M > w _p	280			FILL: TOPSOIL		
		Clayey SAND - fine to coarse grained, pale grey and orange-brown to red-brown, with highly weathered pockets, with fine to coarse grained sub-angular gravel, fines of medium plasticity.					D - M	MD - D			>600	RESIDUAL SOIL	
				1.0			0.80m SANDSTONE - fine to coarse grained, red-brown, estimated medium to high strength. Hole Terminated at 0.81 m Refusal	D				HIGHLY WEATHERED ROCK	
				1.5									
				2.0									


LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition	
Water		U ₅₀	50mm Diameter tube sample	VS	Very Soft	<25	D	Dry
Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M	Moist
Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W	Wet
Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p	Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L	Liquid Limit
Gradational or transitional strata		Field Tests		H	Hard	>400		
Definitive or distinct strata change		PID	Photoionisation detector reading (ppm)	Fb	Friable			
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	Density	V	Very Loose	Density Index <15%	
		HP	Hand Penetrometer test (UCS kPa)	L	Loose		Density Index 15 - 35%	
				MD	Medium Dense		Density Index 35 - 65%	
				D	Dense		Density Index 65 - 85%	
				VD	Very Dense		Density Index 85 - 100%	

ENGINEERING LOG - TEST PIT

CLIENT: McCLOY GROUP
PROJECT: PROPOSED SUBDIVISION - STAGE 7
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP705
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 6-3-18

EQUIPMENT TYPE: 5 TONNE EXCAVATOR
TEST PIT LENGTH: 2.0 m **WIDTH:** 0.3 m
SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered	0.10m				CL	0.05m FILL: Tree Mulch	M				FILL: TREE MULCH
		D					FILL: TOPSOIL - Sandy CLAY - low to medium plasticity, dark grey to dark brown, with some orange fine to coarse grained sand, trace fine to medium grained sub-angular gravel.	M > w _p				FILL: TOPSOIL
		0.20m					SANDSTONE - fine to coarse grained, pale red-brown and pale grey, estimated medium to high strength. Hole terminated at 0.21 m Refusal	D				HIGHLY WEATHERED ROCK
				0.5								
				1.0								
				1.5								
				2.0								

LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition
Water		U ₅₀	50mm Diameter tube sample	VS	Very Soft	<25	D Dry
Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M Moist
Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W Wet
Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L Liquid Limit
Gradational or transitional strata				H	Hard	>400	
Definitive or distinct strata change				Fb	Friable		
Field Tests		PID	Photoionisation detector reading (ppm)	Density		V Very Loose	Density Index <15%
DCP(x-y)			Dynamic penetrometer test (test depth interval shown)	L	Loose		Density Index 15 - 35%
HP			Hand Penetrometer test (UCS kPa)	MD	Medium Dense		Density Index 35 - 65%
				D	Dense		Density Index 65 - 85%
				VD	Very Dense		Density Index 85 - 100%



ENGINEERING LOG - TEST PIT






CLIENT: McCLOY GROUP
PROJECT: PROPOSED SUBDIVISION - STAGE 7
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP706
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 6-3-18

EQUIPMENT TYPE: 5 TONNE EXCAVATOR
TEST PIT LENGTH: 2.0 m **WIDTH:** 0.3 m

SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations	
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result		
E	Not Encountered	0.30m		0.5		SC	0.05m FILL: Tree Mulch	M				FILL: TREE MULCH	
							FILL: TOPSOIL - Clayey SAND - fine to coarse grained, dark grey to dark brown, fines of low to medium plasticity.	M				FILL: TOPSOIL	
		D 0.50m				SC	0.25m Clayey SAND - fine to coarse grained, pale orange-brown and pale grey, with fine to coarse grained sub-angular gravel.	D - M				D	RESIDUAL SOIL
							0.60m SANDSTONE - fine to coarse grained, pale grey and pale red-brown, estimated medium to high strength. Hole Terminated at 0.61 m Refusal	D				HIGHLY WEATHERED ROCK	


LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition
Water		U ₃₀ 50mm Diameter tube sample		VS	Very Soft	<25	D Dry
 Water Level (Date and time shown)		CBR Bulk sample for CBR testing		S	Soft	25 - 50	M Moist
 Water Inflow		E Environmental sample (Glass jar, sealed and chilled on site)		F	Firm	50 - 100	W Wet
 Water Outflow		ASS Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)		St	Stiff	100 - 200	W _p Plastic Limit
Strata Changes		B Bulk Sample		VSt	Very Stiff	200 - 400	W _L Liquid Limit
 Gradational or transitional strata		Field Tests		H	Hard	>400	
 Definitive or distinct strata change		PID Photoionisation detector reading (ppm)		Fb	Friable		
		DCP(x-y) Dynamic penetrometer test (test depth interval shown)		Density	V	Very Loose	Density Index <15%
		HP Hand Penetrometer test (UCS kPa)			L	Loose	Density Index 15 - 35%
					MD	Medium Dense	Density Index 35 - 65%
					D	Dense	Density Index 65 - 85%
					VD	Very Dense	Density Index 85 - 100%

ENGINEERING LOG - TEST PIT

CLIENT: McCLOY GROUP
PROJECT: PROPOSED SUBDIVISION - STAGE 7
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP707
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 6-3-18

EQUIPMENT TYPE: 5 TONNE EXCAVATOR
TEST PIT LENGTH: 2.0 m **WIDTH:** 0.3 m
SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered					SC	0.05m FILL: Tree Mulch FILL: TOPSOIL - Clayey SAND - fine to coarse grained, dark grey to dark brown, fine to medium sub-angular gravel, fines of low to medium plasticity, root affected.	D - M		D		FILL: TREE MULCH FILL: TOPSOIL
				0.35m	Extremely Weathered Sandstone with soil properties: breaks down into Gravelly Sand - fine to coarse grained, pale orange-brown and pale grey, with highly weathered pockets.		EXTREMELY WEATHERED ROCK					
		0.60m		0.5		SP						
		D 0.70m				0.75m 0.77m	SANDSTONE - fine to coarse grained, pale grey and pale red-brown, estimated low to medium strength. Hole Terminated at 0.77 m Refusal	D	HIGHLY WEATHERED ROCK			
				1.0								
				1.5								
				2.0								

LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition	
Water		U ₃₀	50mm Diameter tube sample	VS	Very Soft	<25	D	Dry
Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M	Moist
Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W	Wet
Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p	Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L	Liquid Limit
Gradational or transitional strata		Field Tests		H	Hard	>400		
Definitive or distinct strata change		PID	Photoionisation detector reading (ppm)	Fb	Friable			
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	Density	V	Very Loose	Density Index <15%	
		HP	Hand Penetrometer test (UCS kPa)		L	Loose	Density Index 15 - 35%	
					MD	Medium Dense	Density Index 35 - 65%	
					D	Dense	Density Index 65 - 85%	
					VD	Very Dense	Density Index 85 - 100%	

ENGINEERING LOG - TEST PIT

CLIENT: McCLOY GROUP

PROJECT: PROPOSED SUBDIVISION - STAGE 7

LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO:

TP708

PAGE:

1 OF 1

JOB NO:

NEW15P-0070A

LOGGED BY:

BE

DATE:


6-3-18






EQUIPMENT TYPE: 5 TONNE EXCAVATOR

SURFACE RL:

TEST PIT LENGTH: 2.0 m WIDTH: 0.3 m

DATUM:

Drilling and Sampling					Material description and profile information						Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result		
E	Not Encountered	D	0.30m	0.5		CL	0.03m FILL: Tree Mulch	D - M	M > w _p	MD - D	D - VD	FILL: TREE MULCH	
							FILL: TOPSOIL - Sandy CLAY - low to medium plasticity, dark brown with some dark grey, fine to coarse grained sand, with some fine to medium grained sub-angular gravel.	FILL: TOPSOIL					
							0.20m SC Clayey SAND - fine to coarse grained, pale orange-brown to red-brown and pale grey, fines of low to medium plasticity, fine to medium grained sub-angular to angular gravel.	RESIDUAL SOIL					
							0.25m SP Extremely weathered Sandstone with soil properties: breaks down into Gravelly Sand - fine to coarse grained, pale grey and pale orange, fine to coarse angular to sub-angular gravel, trace clay.	EXTREMELY WEATHERED ROCK					
							0.65m SANDSTONE - fine to coarse grained, pale grey and pale red-brown, estimated low to medium strength. Hole Terminated at 0.66 m Refusal	D				HIGHLY WEATHERED ROCK	
				1.0									
				1.5									
				2.0									

LEGEND:	Notes, Samples and Tests	Consistency	UCS (kPa)	Moisture Condition
	Water	VS Very Soft	<25	D Dry
	 Water Level (Date and time shown)	S Soft	25 - 50	M Moist
	 Water Inflow	F Firm	50 - 100	W Wet
 Water Outflow	St Stiff	100 - 200	W _p Plastic Limit	
Strata Changes	ASS Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	VSt Very Stiff	200 - 400	W _L Liquid Limit
 Gradational or transitional strata	B Bulk Sample	H Hard	>400	
 Definitive or distinct strata change	Field Tests	Fb Friable		
	PID Photoionisation detector reading (ppm)	Density	V Very Loose	Density Index <15%
	DCP(x-y) Dynamic penetrometer test (test depth interval shown)	L Loose		Density Index 15 - 35%
	HP Hand Penetrometer test (UCS kPa)	MD Medium Dense		Density Index 35 - 65%
		D Dense		Density Index 65 - 85%
		VD Verv Dense		Densitiv Index 85 - 100%

LEGEND:

Water

- Water Level (Date and time shown)
- Water Inflow
- Water Outflow

Strata Changes

- Gradational or transitional strata
- Definitive or distinct strata change

Notes, Samples and Tests

- U₃₀ 50mm Diameter tube sample
- CBR Bulk sample for CBR testing
- E Environmental sample (Glass jar, sealed and chilled on site)
- ASS Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)
- B Bulk Sample

Field Tests

- PID Photoionisation detector reading (ppm)
- DCP(x-y) Dynamic penetrometer test (test depth interval shown)
- HP Hand Penetrometer test (UCS kPa)

Consistency

- VS Very Soft <25
- S Soft 25 - 50
- F Firm 50 - 100
- St Stiff 100 - 200
- VSt Very Stiff 200 - 400
- H Hard >400
- Fb Friable

UCS (kPa)

- <25
- 25 - 50
- 50 - 100
- 100 - 200
- 200 - 400
- >400

Moisture Condition

- D Dry
- M Moist
- W Wet
- W_p Plastic Limit
- W_L Liquid Limit

Density


- V Very Loose Density Index <15%
- L Loose Density Index 15 - 35%
- MD Medium Dense Density Index 35 - 65%
- D Dense Density Index 65 - 85%
- VD Very Dense Density Index 85 - 100%






ENGINEERING LOG - TEST PIT

CLIENT: McCLOY GROUP
PROJECT: PROPOSED SUBDIVISION - STAGE 7
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP709
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 6-3-18

EQUIPMENT TYPE: 5 TONNE EXCAVATOR
TEST PIT LENGTH: 2.0 m **WIDTH:** 0.3 m
SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered					CL SP	0.03m FILL: Tree Mulch	M				FILL: TREE MULCH
							FILL: TOPSOIL - Sandy CLAY - low to medium plasticity, dark brown with some dark grey, fine to coarse grained sand, with some fine to medium grained sub-angular gravel.	M > w _p				FILL: TOPSOIL
							0.20m Extremely weathered Sandstone with soil properties: breaks down into Gravelly Sand - fine to coarse grained, pale grey and pale orange, fine to coarse angular to sub-angular gravel, trace clay.	D - M	D - VD			EXTREMELY WEATHERED ROCK
							0.30m 0.33m SANDSTONE - fine to coarse grained, pale grey and pale red-brown, estimated low to medium strength. Hole Terminated at 0.33 m Practical Refusal	D				HIGHLY WEATHERED ROCK
				0.5								
				1.0								
				1.5								
				2.0								


LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition
Water		U ₃₀	50mm Diameter tube sample	VS	Very Soft	<25	D Dry
 Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M Moist
 Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W Wet
 Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L Liquid Limit
 Gradational or transitional strata		Field Tests		H	Hard	>400	
 Definitive or distinct strata change		PID	Photoionisation detector reading (ppm)	Fb	Friable		
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	V	Very Loose	Density Index <15%	
		HP	Hand Penetrometer test (UCS kPa)	L	Loose	Density Index 15 - 35%	
				MD	Medium Dense	Density Index 35 - 65%	
				D	Dense	Density Index 65 - 85%	
				VD	Very Dense	Density Index 85 - 100%	

ENGINEERING LOG - TEST PIT








CLIENT: McCLOY GROUP
PROJECT: PROPOSED SUBDIVISION - STAGE 7
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP710
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 6-3-18

EQUIPMENT TYPE: 5 TONNE EXCAVATOR
TEST PIT LENGTH: 2.0 m **WIDTH:** 0.3 m
SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered					SP	Extremely weathered Sandstone with soil properties: breaks down into Gravelly Sand - fine to coarse grained, pale grey and pale orange, fine to coarse angular to sub-angular gravel, trace clay.	D - M	D - VD			EXTREMELY WEATHERED ROCK
							SANDSTONE - fine to coarse grained, pale grey and pale red-brown, estimated medium to high strength. Hole Terminated at 0.28 m Refusal	D				HIGHLY WEATHERED ROCK
				0.5								
				1.0								
				1.5								
				2.0								

LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition
Water		U ₅₀	50mm Diameter tube sample	VS	Very Soft	<25	D Dry
Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M Moist
Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W Wet
Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L Liquid Limit
Gradational or transitional strata				H	Hard	>400	
Definitive or distinct strata change				Fb	Friable		
		Field Tests		Density			
		PID	Photoionisation detector reading (ppm)	V	Very Loose	Density Index <15%	
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	L	Loose	Density Index 15 - 35%	
		HP	Hand Penetrometer test (UCS kPa)	MD	Medium Dense	Density Index 35 - 65%	
				D	Dense	Density Index 65 - 85%	
				VD	Very Dense	Density Index 85 - 100%	

EQUIPMENT TYPE:		5 TONNE EXCAVATOR		SURFACE RL:									
TEST PIT LENGTH:		2.0 m		WIDTH: 0.3 m									
				DATUM:									
Drilling and Sampling					Material description and profile information				Field Test		Structure and additional observations		
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type		Result	
E	Not Encountered	0.10m				SC	FILL: TOPSOIL - Clayey SAND - fine to coarse grained, pale orange-brown to red-brown and pale grey, fines of low to medium plasticity, fine to medium grained sub-angular to angular gravel.	D - M				FILL: TOPSOIL	
		D											
		0.20m											
		0.40m											
		D											
0.60m	0.5		CH	Extremely weathered Sandstone with soil properties: breaks down into Silty Clay - medium to high plasticity, pale grey and pale orange, with highly weathered pockets.	M < w _p	H			EXTREMELY WEATHERED ROCK				
	1.0												
	1.30m												
	1.35m												
						SANDSTONE - fine to coarse grained, pale grey and pale red-brown, estimated low to medium strength.	D				HIGHLY WEATHERED ROCK		
				1.5			Hole Terminated at 1.35 m Refusal						
				2.0									
LEGEND:			Notes, Samples and Tests					Consistency		UCS (kPa)		Moisture Condition	
Water			U ₅₀ 50mm Diameter tube sample					VS Very Soft		<25		D Dry	
 Water Level			CBR Bulk sample for CBR testing					S Soft		25 - 50		M Moist	
(Date and time shown)			E Environmental sample					F Firm		50 - 100		W Wet	
 Water Inflow			(Glass jar, sealed and chilled on site)					St Stiff		100 - 200		W _p Plastic Limit	
 Water Outflow			ASS Acid Sulfate Soil Sample					VSt Very Stiff		200 - 400		W _L Liquid Limit	
Strata Changes			(Plastic bag, air expelled, chilled)					H Hard		>400			
 Gradational or transitional strata			B Bulk Sample					Fb Friable					
 Definitive or distinct strata change			Field Tests					Density					
			PID Photoionisation detector reading (ppm)					V Very Loose				Density Index <15%	
			DCP(x-y) Dynamic penetrometer test (test depth interval shown)					L Loose				Density Index 15 - 35%	
			HP Hand Penetrometer test (UCS kPa)					MD Medium Dense				Density Index 35 - 65%	
								D Dense				Density Index 65 - 85%	
								VD Very Dense				Density Index 85 - 100%	

ENGINEERING LOG - TEST PIT

CLIENT: McCLOY GROUP
PROJECT: PROPOSED SUBDIVISION - STAGE 7
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP712
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 6-3-18

EQUIPMENT TYPE: 5 TONNE EXCAVATOR
TEST PIT LENGTH: 2.0 m **WIDTH:** 0.3 m

SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations																																																																																								
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result																																																																																									
E	Not Encountered	0.30m	D	0.5		SC	0.03m FILL: Tree Mulch	D - M		HP	>600	FILL: TREE MULCH																																																																																								
						SP	0.06m FILL: TOPSOIL - Clayey SAND - fine to coarse grained, dark grey to dark brown, fines of low to medium plasticity.					FILL: TOPSOIL																																																																																								
		GP	0.10m FILL: Gravelly SAND - fine to coarse grained, grey, fine grained angular to sub-angular gravel.			FILL																																																																																														
		0.50m					CH	0.25m FILL: Sandy GRAVEL - fine to medium grained, angular to sub-angular, dark brown. Sandy CLAY - medium to high plasticity, brown and pale grey, fine to coarse grained sand.	M ~ w _p	H	HP	>600	RESIDUAL SOIL																																																																																							
													CH	0.50m Silty CLAY - medium to high plasticity, pale grey and pale orange-brown, with extremely weathered sandstone pockets.																																																																																						
							CH	1.10m SANDSTONE - fine to coarse grained, pale grey and pale red-brown, estimated low to medium strength.	D				HIGHLY WEATHERED ROCK																																																																																							
													1.15m	Hole Terminated at 1.15 m Refusal																																																																																						
								1.5																																																																																												

LEGEND: Water Water Level (Date and time shown) Water Inflow Water Outflow Strata Changes Gradational or transitional strata Definitive or distinct strata change	Notes, Samples and Tests U ₅₀ 50mm Diameter tube sample CBR Bulk sample for CBR testing E Environmental sample (Glass jar, sealed and chilled on site) ASS Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled) B Bulk Sample Field Tests PID Photoionisation detector reading (ppm) DCP(x-y) Dynamic penetrometer test (test depth interval shown) HP Hand Penetrometer test (UCS kPa)	Consistency VS Very Soft S Soft F Firm St Stiff VSt Very Stiff H Hard Fb Friable Density V Very Loose L Loose MD Medium Dense D Dense VD Very Dense	UCS (kPa) <25 25 - 50 50 - 100 100 - 200 200 - 400 >400	Moisture Condition D Dry M Moist W Wet W _p Plastic Limit W _L Liquid Limit Density Index <15% Density Index 15 - 35% Density Index 35 - 65% Density Index 65 - 85% Density Index 85 - 100%				

ENGINEERING LOG - TEST PIT

CLIENT: McCLOY GROUP

PROJECT: PROPOSED SUBDIVISION - STAGE 7

LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO:

TP713

PAGE:

1 OF 1

JOB NO:

NEW15P-0070A

LOGGED BY:

BE

DATE:


6-3-18






EQUIPMENT TYPE: 5 TONNE EXCAVATOR

SURFACE RL:

TEST PIT LENGTH: 2.0 m WIDTH: 0.3 m

DATUM:

Drilling and Sampling					Material description and profile information						Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result		
E	Not Encountered					SC	0.05m FILL: Tree Mulch	D - M				FILL: TREE MULCH	
							FILL: TOPSOIL - Clayey SAND - fine to coarse grained, pale grey, root affected.					FILL: TOPSOIL	
							0.25m			0.30m SANDSTONE - fine to coarse grained, pale grey and pale red-brown, estimated medium to high strength.	D		HIGHLY WEATHERED ROCK
				0.5			Hole Terminated at 0.30 m Refusal						
				1.0									
				1.5									
				2.0									

LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition	
Water		U ₃₀	50mm Diameter tube sample	VS	Very Soft	<25	D	Dry
 Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M	Moist
 Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W	Wet
 Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p	Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L	Liquid Limit
 Gradational or transitional strata		Field Tests		H	Hard	>400		
 Definitive or distinct strata change		PID	Photoionisation detector reading (ppm)	Fb	Friable			
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	V	Very Loose		Density Index <15%	
		HP	Hand Penetrometer test (UCS kPa)	L	Loose		Density Index 15 - 35%	
				MD	Medium Dense		Density Index 35 - 65%	
				D	Dense		Density Index 65 - 85%	
				VD	Very Dense		Density Index 85 - 100%	



ENGINEERING LOG - TEST PIT

CLIENT: McCLOY GROUP
PROJECT: PROPOSED SUBDIVISION - STAGE 7
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP714
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 6-3-18

EQUIPMENT TYPE: 5 TONNE EXCAVATOR
TEST PIT LENGTH: 2.0 m **WIDTH:** 0.3 m

SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered					SM	0.05m FILL: Tree Mulch FILL: TOPSOIL - Clayey SAND - Fine to coarse grained, pale grey, fines of low to medium plasticity, root affected.	D - M				FILL: TREE MULCH FILL: TOPSOIL
		0.30m D 0.50m			CH	0.25m Extremely weathered Sandstone with soil properties: breaks down into Silty Clay - medium to high plasticity, pale grey and pale orange. with highly weathered sandstone pockets.	M < w _p	H	EXTREMELY WEATHERED ROCK			
				1.5			Hole Terminated at 1.40 m Very slow progress					
				2.0								






LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition
Water		U ₃₀	50mm Diameter tube sample	VS	Very Soft	<25	D Dry
Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M Moist
Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W Wet
Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L Liquid Limit
Gradational or transitional strata		Field Tests		H	Hard	>400	
Definitive or distinct strata change		PID	Photoionisation detector reading (ppm)	Fb	Friable		
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	V	Very Loose	Density Index <15%	
		HP	Hand Penetrometer test (UCS kPa)	L	Loose	Density Index 15 - 35%	
				MD	Medium Dense	Density Index 35 - 65%	
				D	Dense	Density Index 65 - 85%	
				VD	Very Dense	Density Index 85 - 100%	

ENGINEERING LOG - TEST PIT

CLIENT: MCCLOY GROUP DEVELOPMENT MANAGEMENT PTY LTD
PROJECT: PROPOSED SUBDIVISION - STAGES 5 TO 9
LOCATION: PITT STREET, TERALBA

TEST PIT NO: TP105
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: SJK
DATE: 13-1-16

EQUIPMENT TYPE: 22 tonne excavator
TEST PIT LENGTH: 3.0 m **WIDTH:** 1.5 m
SURFACE RL: 39.0 m
DATUM: Assumed

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations		
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result			
E	Not Encountered					CH	CLAY - medium to high plasticity, pale brown, some fine to medium grained sand, root affected.	M > w _p	VSt	HP	250	TOPSOIL / RESIDUAL SOIL		
		0.40m												RESIDUAL SOIL
		U50	38.5	0.5		CH	CLAY - medium to high plasticity, pale grey and pale brown, some fine to medium grained sand, trace of fine to coarse grained angular gravel (sandy siltstone).			HP	270			
		0.80m									HP	450		
			38.0	1.0			Sandy SILTSTONE - grey to pale grey with pale brown to orange, sand mostly fine grained, estimated low to medium strength, semi-fractured.	M				HIGHLY WEATHERED ROCK		
			37.5	1.5										
			37.0	2.0			Silty SANDSTONE - mostly fine grained, pale brown with grey, estimated medium strength.			D				
							2.30m							
			36.5	2.5			Hole Terminated at 2.30 m Slow progress							


LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition	
Water		U ₅₀	50mm Diameter tube sample	VS	Very Soft	<25	D	Dry
Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M	Moist
Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W	Wet
Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p	Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L	Liquid Limit
Gradational or transitional strata				H	Hard	>400		
Definitive or distinct strata change				Fb	Friable			
		Field Tests		Density				
		PID	Photoionisation detector reading (ppm)	V	Very Loose		Density Index <15%	
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	L	Loose		Density Index 15 - 35%	
		HP	Hand Penetrometer test (UCS kPa)	MD	Medium Dense		Density Index 35 - 65%	
				D	Dense		Density Index 65 - 85%	
				VD	Very Dense		Density Index 85 - 100%	

ENGINEERING LOG - TEST PIT

CLIENT: MCCLOY GROUP DEVELOPMENT MANAGEMENT PTY LTD
PROJECT: PROPOSED SUBDIVISION - STAGES 5 TO 9
LOCATION: PITT STREET, TERALBA




TEST PIT NO: TP107
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: SJK
DATE: 12-1-16

EQUIPMENT TYPE: 22 tonne excavator
TEST PIT LENGTH: 3.0 m **WIDTH:** 1.5 m
SURFACE RL: 34.5 m
DATUM: Assumed



Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered		34.0	0.5		SM	Silty SAND - fine to coarse grained, brown to grey, fines of low plasticity, root affected.	M				TOPSOIL
						CH	CLAY - medium to high plasticity, pale brown to orange and pale grey, trace to some fine to medium grained sand.	M > W _p	VSt			RESIDUAL SOIL
							Interbedded SILTSTONE and SANDSTONE - grey to pale grey with orange, fine to medium grained sand, estimated high strength, fractured.	D to M				HIGHLY WEATHERED ROCK
							Hole Terminated at 0.75 m Practical Refusal					
			33.5	1.0								
			33.0	1.5								
			32.5	2.0								
			32.0	2.5								

LEGEND:

Water

-  Water Level (Date and time shown)
-  Water Inflow
-  Water Outflow

Strata Changes

-  Gradational or transitional strata
-  Definitive or distinct strata change

Notes, Samples and Tests

- U₅₀ 50mm Diameter tube sample
- CBR Bulk sample for CBR testing
- E Environmental sample (Glass jar, sealed and chilled on site)
- ASS Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)
- B Bulk Sample

Field Tests

- PID Photoionisation detector reading (ppm)
- DCP(x-y) Dynamic penetrometer test (test depth interval shown)
- HP Hand Penetrometer test (UCS kPa)

Consistency

- VS Very Soft
- S Soft
- F Firm
- St Stiff
- VSt Very Stiff
- H Hard
- Fb Friable

UCS (kPa)

- <25
- 25 - 50
- 50 - 100
- 100 - 200
- 200 - 400
- >400

Moisture Condition

- D Dry
- M Moist
- W Wet
- W_p Plastic Limit
- W_L Liquid Limit

Density

- V Very Loose
- L Loose
- MD Medium Dense
- D Dense
- VD Very Dense


- Density Index <15%
- Density Index 15 - 35%
- Density Index 35 - 65%
- Density Index 65 - 85%
- Density Index 85 - 100%




ENGINEERING LOG - TEST PIT









CLIENT: MCCLOY GROUP DEVELOPMENT MANAGEMENT PTY LTD
PROJECT: PROPOSED SUBDIVISION - STAGES 5 TO 9
LOCATION: PITT STREET, TERALBA

TEST PIT NO: TP108
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: SJK
DATE: 13-1-16

EQUIPMENT TYPE: 22 tonne excavator
TEST PIT LENGTH: 3.0 m **WIDTH:** 1.5 m
SURFACE RL: 35.0 m
DATUM: Assumed

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations	
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result		
E	Not Encountered		34.5	0.5		SC	Clayey SAND - fine to coarse grained, dark brown to grey, fines of low to medium plasticity, trace of fine grained gravel, root affected.	M		HP	150	TOPSOIL	
					CH	CLAY / Sandy CLAY - medium to high plasticity, pale brown to orange with grey, fine to medium grained sand, some tree roots.	M > w _p	St	RESIDUAL SOIL				
						SANDSTONE - fine to medium grained, pale brown to orange, pale grey to white and brown to red, estimated high strength. Hole Terminated at 0.80 m Refusal	D		HIGHLY WEATHERED ROCK				
			34.0	1.0									
			33.5	1.5									
			33.0	2.0									
			32.5	2.5									

LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition
Water		U ₃₀ 50mm Diameter tube sample		VS	Very Soft	<25	D Dry
 Water Level (Date and time shown)		CBR Bulk sample for CBR testing		S	Soft	25 - 50	M Moist
 Water Inflow		E Environmental sample (Glass jar, sealed and chilled on site)		F	Firm	50 - 100	W Wet
 Water Outflow		ASS Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)		St	Stiff	100 - 200	W _p Plastic Limit
Strata Changes		B Bulk Sample		VSt	Very Stiff	200 - 400	W _L Liquid Limit
--- Gradational or transitional strata		Field Tests		H	Hard	>400	
— Definitive or distinct strata change		PID Photoionisation detector reading (ppm)		Fb	Friable		
		DCP(x-y) Dynamic penetrometer test (test depth interval shown)		Density		V Very Loose	Density Index <15%
		HP Hand Penetrometer test (UCS kPa)		L	Loose	MD Medium Dense	Density Index 15 - 35%
				D	Dense	D	Density Index 35 - 65%
				VD	Very Dense	D	Density Index 65 - 85%
						D	Density Index 85 - 100%







EQUIPMENT TYPE:		22 tonne excavator		SURFACE RL:		34.0 m							
TEST PIT LENGTH:		3.0 m		WIDTH:		1.5 m							
DATUM:		Assumed											
Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations	
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics,colour,minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result		
E	Not Encountered		33.5	0.5		SC	0.15m Clayey SAND - fine to coarse grained, dark brown to grey, fines of low to medium plasticity, trace of fine grained gravel, root affected.	M		HP	150	TOPSOIL	
						CI	0.45m Sandy CLAY - medium plasticity, pale brown, fine to medium grained sand, some tree roots.	M > w _p	St			RESIDUAL SOIL	
							0.50m SANDSTONE - fine to medium grained, pale brown and pale grey, estimated high strength.	D				HIGHLY WEATHERED ROCK	
							Hole Terminated at 0.50 m Refusal						
			33.0	1.0									
			32.5	1.5									
			32.0	2.0									
			31.5	2.5									
LEGEND:					Notes, Samples and Tests					Consistency		UCS (kPa)	Moisture Condition
Water					U ₅₀ 50mm Diameter tube sample					VS Very Soft		<25	D Dry
 Water Level (Date and time shown)					CBR Bulk sample for CBR testing					S Soft		25 - 50	M Moist
 Water Inflow					E Environmental sample (Glass jar, sealed and chilled on site)					F Firm		50 - 100	W Wet
 Water Outflow					ASS Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)					St Stiff		100 - 200	W _p Plastic Limit
Strata Changes					B Bulk Sample					VSt Very Stiff		200 - 400	W _L Liquid Limit
 Gradational or transitional strata					Field Tests					H Hard		>400	
 Definitive or distinct strata change					PID Photoionisation detector reading (ppm)					Density		V Very Loose	Density Index <15%
					DCP(x-y) Dynamic penetrometer test (test depth interval shown)					L Loose			Density Index 15 - 35%
					HP Hand Penetrometer test (UCS kPa)					MD Medium Dense			Density Index 35 - 65%
										D Dense			Density Index 65 - 85%
										VD Very Dense			Density Index 85 - 100%






ENGINEERING LOG - TEST PIT

CLIENT: MCCLOY GROUP DEVELOPMENT MANAGEMENT PTY LTD
PROJECT: PROPOSED SUBDIVISION - STAGES 5 TO 9
LOCATION: PITT STREET, TERALBA

TEST PIT NO: TP112
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: SJK
DATE: 12-1-16

EQUIPMENT TYPE: 22 tonne excavator
TEST PIT LENGTH: 3.0 m **WIDTH:** 1.5 m
SURFACE RL: 31.5 m
DATUM: Assumed

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations	
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result		
E	Not Encountered	0.30m	31.0	0.5		SC	Clayey SAND - fine to coarse grained, dark brown to grey, fines of low to medium plasticity, trace of fine grained gravel, root affected.	M		HP	200	TOPSOIL	
		0.40m U50				CI	Sandy CLAY - medium plasticity, pale brown, fine to medium grained sand, some tree roots.	M > w _p	St / VSt			RESIDUAL SOIL	
		0.55m CBR											Refusal at eastern end.
		0.65m											
							SANDSTONE - fine to medium grained, pale brown and pale grey, estimated high strength.	D				HIGHLY WEATHERED ROCK	
			30.5	1.0			Hole Terminated at 0.90 m Refusal						
			30.0	1.5									
			29.5	2.0									
			29.0	2.5									
LEGEND:			Notes, Samples and Tests					Consistency		UCS (kPa)		Moisture Condition	
Water			U ₅₀ 50mm Diameter tube sample					VS Very Soft		<25		D Dry	
 Water Level			CBR Bulk sample for CBR testing					S Soft		25 - 50		M Moist	
(Date and time shown)			E Environmental sample					F Firm		50 - 100		W Wet	
 Water Inflow			(Glass jar, sealed and chilled on site)					St Stiff		100 - 200		W _p Plastic Limit	
 Water Outflow			ASS Acid Sulfate Soil Sample					VSt Very Stiff		200 - 400		W _L Liquid Limit	
Strata Changes			B Bulk Sample					H Hard		>400			
 Gradational or transitional strata			Field Tests					Density		V Very Loose		Density Index <15%	
 Definitive or distinct strata change			PID Photoionisation detector reading (ppm)					L Loose				Density Index 15 - 35%	
			DCP(x-y) Dynamic penetrometer test (test depth interval shown)					MD Medium Dense				Density Index 35 - 65%	
			HP Hand Penetrometer test (UCS kPa)					D Dense				Density Index 65 - 85%	
								VD Very Dense				Density Index 85 - 100%	

LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition	
Water		U ₅₀	50mm Diameter tube sample	VS	Very Soft	<25	D	Dry
 Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M	Moist
 Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W	Wet
 Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p	Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L	Liquid Limit
 Gradational or transitional strata		Field Tests		H	Hard	>400		
 Definitive or distinct strata change		PID	Photoionisation detector reading (ppm)	Fb	Friable			
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	Density		V	Very Loose	Density Index <15%
		HP	Hand Penetrometer test (UCS kPa)	L	Loose	MD	Medium Dense	Density Index 15 - 35%
				D	Dense	D	Dense	Density Index 35 - 65%
				VD	Very Dense			Density Index 65 - 85%
								Density Index 85 - 100%



ENGINEERING LOG - TEST PIT

CLIENT: McCLOY DEVELOPMENT MANAGEMENT
PROJECT: PROPOSED SUBDIVISION - STAGES 6 & 9
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP601
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 24-10-17

EQUIPMENT TYPE: 2.5 TONNE EXCAVATOR
TEST PIT LENGTH: 1.5 m **WIDTH:** 0.5 m

SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered	0.25m				SM	TOPSOIL: Silty SAND - fine to coarse grained, grey, fines of low plasticity, root affected.	D				TOPSOIL
					SANDSTONE - fine to coarse grained, red-brown and pale grey, estimated medium strength.		HIGHLY WEATHERED ROCK					
				0.5			Hole Terminated at 0.35 m Practical Refusal					
				1.0								
				1.5								
				2.0								

LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition	
Water		U ₅₀	50mm Diameter tube sample	VS	Very Soft	<25	D	Dry
Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M	Moist
Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W	Wet
Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p	Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L	Liquid Limit
Gradational or transitional strata		Field Tests		H	Hard	>400		
Definitive or distinct strata change		PID	Photoionisation detector reading (ppm)	Fb	Friable			
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	V	Very Loose		Density Index <15%	
		HP	Hand Penetrometer test (UCS kPa)	L	Loose		Density Index 15 - 35%	
				MD	Medium Dense		Density Index 35 - 65%	
				D	Dense		Density Index 65 - 85%	
				VD	Very Dense		Density Index 85 - 100%	



ENGINEERING LOG - TEST PIT

CLIENT: McCLOY DEVELOPMENT MANAGEMENT
PROJECT: PROPOSED SUBDIVISION - STAGES 6 & 9
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP602
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 24-10-17

EQUIPMENT TYPE: 2.5 TONNE EXCAVATOR
TEST PIT LENGTH: 1.5 m **WIDTH:** 0.5 m

SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered					SM	0.05m FILL: TREE MULCH	M				FILL - MULCH
		0.20m				0.20m FILL: TOPSOIL- Silty SAND - fine to coarse grained, dark grey, fines of low plasticity, with some fine to medium grained sub-angular to sub-rounded gravel, root affected.					FILL - TOPSOIL	
		0.25m				SP	0.25m Clayey SAND - fine to coarse grained, orange-brown and pale grey-white, trace fine to medium grained sub-angular to sub-rounded gravel.		D		RESIDUAL SOIL / POSSIBLE COLLUVIUM	
		D				0.27m SANDSTONE - fine to coarse grained, pale orange-brown and pale grey-white, estimated medium to high strength.					HIGHLY WEATHERED ROCK	
				0.5			Hole Terminated at 0.27 m Practical Refusal					
				1.0								
				1.5								
				2.0								

LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition
Water		U ₅₀	50mm Diameter tube sample	VS	Very Soft	<25	D Dry
Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M Moist
Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W Wet
Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L Liquid Limit
Gradational or transitional strata				H	Hard	>400	
Definitive or distinct strata change				Fb	Friable		
		Field Tests		Density			
		PID	Photoionisation detector reading (ppm)	V	Very Loose	Density Index <15%	
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	L	Loose	Density Index 15 - 35%	
		HP	Hand Penetrometer test (UCS kPa)	MD	Medium Dense	Density Index 35 - 65%	
				D	Dense	Density Index 65 - 85%	
				VD	Very Dense	Density Index 85 - 100%	


ENGINEERING LOG - TEST PIT






CLIENT: McCLOY DEVELOPMENT MANAGEMENT
PROJECT: PROPOSED SUBDIVISION - STAGES 6 & 9
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP903
PAGE: 1 OF 1
JOB NO: NEW15P-0070A
LOGGED BY: BE
DATE: 24-10-17

EQUIPMENT TYPE: 2.5 TONNE EXCAVATOR
TEST PIT LENGTH: 1.5 m **WIDTH:** 0.5 m

SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered					SC	0.05m FILL: TREE MULCH	M				FILL - MULCH
							FILL-TOPSOIL: Clayey SAND - fine to coarse grained, dark grey, fines of low to medium plasticity, with some fine to medium grained sub-angular to sub-rounded gravel.	M - W				FILL - TOPSOIL
							0.20m					
							0.25m SANDSTONE - fine to coarse grained, pale orange-brown and pale grey-white, estimated medium to high strength. Hole Terminated at 0.25 m Practical Refusal	D	VD			HIGHLY WEATHERED ROCK
				0.5								
				1.0								
				1.5								
				2.0								


LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition
Water		U ₅₀	50mm Diameter tube sample	VS	Very Soft	<25	D Dry
 Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M Moist
 Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W Wet
 Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L Liquid Limit
 Gradational or transitional strata		Field Tests		H	Hard	>400	
 Definitive or distinct strata change		PID	Photoionisation detector reading (ppm)	Fb	Friable		
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	Density	V	Very Loose	Density Index <15%
		HP	Hand Penetrometer test (UCS kPa)	L	Loose		Density Index 15 - 35%
				MD	Medium Dense		Density Index 35 - 65%
				D	Dense		Density Index 65 - 85%
				VD	Very Dense		Density Index 85 - 100%






ENGINEERING LOG - TEST PIT

CLIENT: McCLOY TERALBA
PROJECT: PROPOSED SUBDIVISION - STAGE 8
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP204
PAGE: 1 OF 1
JOB NO: NEW15P - 0070A
LOGGED BY: BE
DATE: 13-5-16

EQUIPMENT TYPE: KOBELCO - 5.5 Tonne Excavator
TEST PIT LENGTH: 2.0 m **WIDTH:** 0.3 m
SURFACE RL: 31.5 m
DATUM: Assumed

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered	0.30m	31.0	0.5		SM	Silty SAND - fine to medium grained, grey, root affected.	D - M		HP	>600	TOPSOIL
		0.40m				SP	SAND - fine to medium grained, grey to yellow-brown.	MD - D				COLLUVIUM
		0.40m				CI	Sandy CLAY - medium to high plasticity, orange and orange-brown, fine to medium grained sand.	M < w _L	H			RESIDUAL SOIL
		0.65m					SANDSTONE - fine to medium grained, pale orange and white, low plasticity, estimated very low to low strength.	D - M				EXTREMELY TO HIGHLY WEATHERED ROCK
							Hole Terminated at 0.65 m Refusal on weathered rock					
			30.5	1.0								
			30.0	1.5								
			29.5	2.0								
			29.0	2.5								



LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition
Water		U ₅₀ 50mm Diameter tube sample		VS	Very Soft	<25	D Dry
 Water Level (Date and time shown)		CBR Bulk sample for CBR testing		S	Soft	25 - 50	M Moist
 Water Inflow		E Environmental sample (Glass jar, sealed and chilled on site)		F	Firm	50 - 100	W Wet
 Water Outflow		ASS Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)		St	Stiff	100 - 200	W _p Plastic Limit
Strata Changes		B Bulk Sample		VSt	Very Stiff	200 - 400	W _L Liquid Limit
 Gradational or transitional strata		Field Tests		H	Hard	>400	
 Definitive or distinct strata change		PID Photoionisation detector reading (ppm)		Fb	Friable		
		DCP(x-y) Dynamic penetrometer test (test depth interval shown)		Density	V Very Loose		Density Index <15%
		HP Hand Penetrometer test (UCS kPa)			L Loose		Density Index 15 - 35%
					MD Medium Dense		Density Index 35 - 65%
					D Dense		Density Index 65 - 85%
					VD Very Dense		Density Index 85 - 100%






ENGINEERING LOG - TEST PIT

CLIENT: McCLOY TERALBA
PROJECT: PROPOSED SUBDIVISION - STAGE 5
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP5-3
PAGE: 1 OF 1
JOB NO: NEW15P - 0070A
LOGGED BY: SJK
DATE: 28-7-17

EQUIPMENT TYPE: 5 TONNE EXCAVATOR
TEST PIT LENGTH: 1.5 m **WIDTH:** 0.5 m
SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result	
E	Not Encountered	U50		0.5		SC	0.05m FILL: MULCH - grey to brown.	M				FILL - MULCH
							FILL-TOPSOIL: Clayey SAND - fine to coarse grained, grey, fines of low to medium plasticity, with some fine to medium grained gravel and organics.					FILL - TOPSOIL
						CI	0.20m FILL: Sandy CLAY / Gravelly Clayey SAND - medium plasticity, grey to brown, with brown to orange and pale grey, fine to coarse grained sand, with some fine to coarse grained gravel, trace cobble sized rock fragments.	M ~ w _p	VSt			CONTROLLED FILL
							0.65m FILL: Silty Gravelly SAND - fine to coarse grained, pale brown with pale grey to white, fine to coarse grained gravel, fines of low plasticity, with some cobble sized rock fragments.					
						CI	0.95m Sandy CLAY - medium to high plasticity, brown to red, pale grey and orange to brown, fine to medium grained sand.	M > w _p	VSt	HP	300	RESIDUAL SOIL
		HP	290									
				1.5		1.50m	Hole Terminated at 1.50 m					
				2.0								
				2.5								



LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition	
Water		U ₅₀	50mm Diameter tube sample	VS	Very Soft	<25	D	Dry
 Water Level (Date and time shown)		CBR	Bulk sample for CBR testing	S	Soft	25 - 50	M	Moist
 Water Inflow		E	Environmental sample (Glass jar, sealed and chilled on site)	F	Firm	50 - 100	W	Wet
 Water Outflow		ASS	Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)	St	Stiff	100 - 200	W _p	Plastic Limit
Strata Changes		B	Bulk Sample	VSt	Very Stiff	200 - 400	W _L	Liquid Limit
 Gradational or transitional strata		Field Tests		H	Hard	>400		
 Definitive or distinct strata change		PID	Photoionisation detector reading (ppm)	Fb	Friable			
		DCP(x-y)	Dynamic penetrometer test (test depth interval shown)	Density	V	Very Loose	Density Index <15%	
		HP	Hand Penetrometer test (UCS kPa)		L	Loose	Density Index 15 - 35%	
					MD	Medium Dense	Density Index 35 - 65%	
					D	Dense	Density Index 65 - 85%	
					VD	Very Dense	Density Index 85 - 100%	

ENGINEERING LOG - TEST PIT

CLIENT: McCLOY TERALBA
PROJECT: PROPOSED SUBDIVISION - STAGE 5
LOCATION: FISHERMANS DRIVE, TERALBA

TEST PIT NO: TP5-5
PAGE: 1 OF 1
JOB NO: NEW15P - 0070A
LOGGED BY: SJK
DATE: 28-7-17

EQUIPMENT TYPE: CASE BACKHOE 580ST
TEST PIT LENGTH: 1.5 m **WIDTH:** 0.5 m
SURFACE RL:
DATUM:

Drilling and Sampling					Material description and profile information					Field Test		Structure and additional observations		
METHOD	WATER	SAMPLES	RL (m)	DEPTH (m)	GRAPHIC LOG	CLASSIFICATION SYMBOL	MATERIAL DESCRIPTION: Soil type, plasticity/particle characteristics, colour, minor components	MOISTURE CONDITION	CONSISTENCY DENSITY	Test Type	Result			
BH	Not Encountered	0.40m	U50	0.5		SC	0.05m FILL: MULCH - grey to brown FILL-TOPSOIL: Clayey SAND - fine to coarse grained, grey, fines of low to medium plasticity, with some fine to medium grained gravel and organics.	M		HP	350	FILL - MULCH		
							M - W	FILL - TOPSOIL						
		0.80m				CH	FILL: Sandy CLAY - medium to high plasticity, pale brown to orange, brown to red, pale grey, fine to coarse grained sand, some fine to coarse grained sub-angular gravel.	M > w _p	VSt			HP	350	CONTROLLED FILL
												HP	350	
				1.0		CH	1.20m CLAY - medium to high plasticity, pale brown with brown to red and grey, with some fine to medium grained sand.	St - VSt	HP	200	RESIDUAL SOIL			
				1.40m		Hole Terminated at 1.40 m								
				1.5										
				2.0										
				2.5										

LEGEND:		Notes, Samples and Tests		Consistency		UCS (kPa)	Moisture Condition
Water		U ₃₀ 50mm Diameter tube sample		VS	Very Soft	<25	D Dry
Water Level (Date and time shown)		CBR Bulk sample for CBR testing		S	Soft	25 - 50	M Moist
Water Inflow		E Environmental sample (Glass jar, sealed and chilled on site)		F	Firm	50 - 100	W Wet
Water Outflow		ASS Acid Sulfate Soil Sample (Plastic bag, air expelled, chilled)		St	Stiff	100 - 200	W _p Plastic Limit
Strata Changes		B Bulk Sample		VSt	Very Stiff	200 - 400	W _L Liquid Limit
Gradational or transitional strata		Field Tests		H	Hard	>400	
Definitive or distinct strata change		PID Photoionisation detector reading (ppm)		Fb	Friable		
		DCP(x-y) Dynamic penetrometer test (test depth interval shown)		Density		V Very Loose	Density Index <15%
		HP Hand Penetrometer test (UCS kPa)		L	Loose	MD Medium Dense	Density Index 15 - 35%
				D	Dense	D	Density Index 35 - 65%
				VD	Very Dense	D	Density Index 65 - 85%
						D	Density Index 85 - 100%

APPENDIX B:

Results of Laboratory Testing

Material Test Report

Report No: MAT:NEW18W-0698--S01

Issue No: 2

This report replaces all previous issues of report no 'MAT:NEW18W-0698--S01'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 7



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 16/03/2018

Sample Details

Sample ID: NEW18W-0698--S01
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 06/03/2018
Source: On-Site
Material: Silty Clay
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP-701 - (0.8 - 1.0m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	9.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	52	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	17	
Plasticity Index (%)	AS 1289.3.3.1	35	

Comments

N/A

Material Test Report

Report No: MAT:NEW18W-0698--S02

Issue No: 2

This report replaces all previous issues of report no 'MAT:NEW18W-0698--S02'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 7



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 16/03/2018

Sample Details

Sample ID: NEW18W-0698--S02
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 06/03/2018
Source: On-Site
Material: Clayey Sand
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP-702 - (0.4 - 0.6m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	7.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	39	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	18	
Plasticity Index (%)	AS 1289.3.3.1	21	

Comments

N/A

Material Test Report

Report No: MAT:NEW18W-0698--S03

Issue No: 2

This report replaces all previous issues of report no 'MAT:NEW18W-0698--S03'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 7



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 16/03/2018

Sample Details

Sample ID: NEW18W-0698--S03
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 06/03/2018
Source: On-Site
Material: Sandy Clay
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP-703 - (0.05 - 0.2m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	3.5	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	24	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	16	
Plasticity Index (%)	AS 1289.3.3.1	8	

Comments

N/A

Material Test Report

Report No: MAT:NEW18W-0698--S04

Issue No: 2

This report replaces all previous issues of report no 'MAT:NEW18W-0698--S04'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 7



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 16/03/2018

Sample Details

Sample ID: NEW18W-0698--S04
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 06/03/2018
Source: On-Site
Material: Clayey Sand
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP-704 - (0.2 - 0.4m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	4.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	26	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	17	
Plasticity Index (%)	AS 1289.3.3.1	9	

Comments

N/A

Material Test Report

Report No: MAT:NEW18W-0698--S05

Issue No: 2

This report replaces all previous issues of report no 'MAT:NEW18W-0698--S05'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 7



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

[Signature]
Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 16/03/2018

Sample Details

Sample ID: NEW18W-0698--S05
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 06/03/2018
Source: On-Site
Material: Sandy Clay
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP-705 - (0.1 - 0.2m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	3.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	24	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	18	
Plasticity Index (%)	AS 1289.3.3.1	6	

Comments

N/A

Material Test Report

Report No: MAT:NEW18W-0698--S06

Issue No: 2

This report replaces all previous issues of report no 'MAT:NEW18W-0698--S06'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 7



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards


Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 16/03/2018

Sample Details

Sample ID: NEW18W-0698--S06
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 06/03/2018
Source: On-Site
Material: Clayey Sand
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP-706 - (0.3 - 0.5m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	3.5	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	27	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	17	
Plasticity Index (%)	AS 1289.3.3.1	10	

Comments

N/A

Report No: MAT:NEW18W-0698--S07

Issue No: 1

Material Test Report

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stages 6 & 9



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 14/03/2018

Sample Details

Sample ID: NEW18W-0698--S07

Sampling Method: AS1289.1.2.1 cl 6.4b

Date Sampled: 06/03/2018

Source: On-Site

Material: Sandstone

Specification: No Specification

Project Location: Pitt Street, Teralba

Sample Location: TP-707 - (0.6 - 0.7m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	5.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	30	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	15	
Plasticity Index (%)	AS 1289.3.3.1	15	

Comments

N/A

Material Test Report

Report No: MAT:NEW18W-0698--S08

Issue No: 2

This report replaces all previous issues of report no 'MAT:NEW18W-0698--S08'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 7



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 16/03/2018

Sample Details

Sample ID: NEW18W-0698--S08
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 06/03/2018
Source: On-Site
Material: Sandstone
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP-708 - (0.3 - 0.5m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	4.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	26	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	16	
Plasticity Index (%)	AS 1289.3.3.1	10	

Comments

N/A

Material Test Report

Report No: MAT:NEW18W-0698--S09

Issue No: 2

This report replaces all previous issues of report no 'MAT:NEW18W-0698--S09'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 7



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 16/03/2018

Sample Details

Sample ID: NEW18W-0698--S09
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 06/03/2018
Source: On-Site
Material: Clayey Sand
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP-711 - (0.1 - 0.2m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	3.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	26	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	19	
Plasticity Index (%)	AS 1289.3.3.1	7	

Comments

N/A

Material Test Report

Report No: MAT:NEW18W-0698--S10

Issue No: 2

This report replaces all previous issues of report no 'MAT:NEW18W-0698--S10'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 7



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 16/03/2018

Sample Details

Sample ID: NEW18W-0698--S10
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 06/03/2018
Source: On-Site
Material: Sandy Siltstone
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP711 - (0.4 - 0.6m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	7.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	36	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	16	
Plasticity Index (%)	AS 1289.3.3.1	20	

Comments

N/A

Material Test Report

Report No: MAT:NEW18W-0698--S11

Issue No: 2

This report replaces all previous issues of report no 'MAT:NEW18W-0698--S11'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 7



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 16/03/2018

Sample Details

Sample ID: NEW18W-0698--S11
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 06/03/2018
Source: On-Site
Material: Sandy Clay
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP712 - (0.3 - 0.5m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	9.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	52	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	21	
Plasticity Index (%)	AS 1289.3.3.1	31	

Comments

N/A

Material Test Report

Report No: MAT:NEW18W-0698--S12

Issue No: 2

This report replaces all previous issues of report no 'MAT:NEW18W-0698--S12'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 7



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 16/03/2018

Sample Details

Sample ID: NEW18W-0698--S12
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 06/03/2018
Source: On-Site
Material: Sandy Siltstone
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP714 - (0.3 - 0.5m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	7.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	43	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	20	
Plasticity Index (%)	AS 1289.3.3.1	23	

Comments

N/A

Material Test Report

Report No: MAT:NEW16W-1263--S11

Issue No: 2


This report replaces all previous issues of report no 'MAT:NEW16W-1263--S11'.

Client: McCloy Teralba Pty Ltd
Suite 1, Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 5 to 9



Accredited for compliance with ISO/IEC 17025
The results of the tests, calibrations and/or
measurements included in this document are traceable
to Australian/national standards

Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 8/06/2016

Sample Details

Sample ID: NEW16W-1263--S11

Sampling Method: AS1289.1.2.1 cl 6.5

Date Sampled: 13/05/2016

Source: On-Site

Material: Sandy Clay

Specification: No Specification

Project Location: Pitt Street, Teralba

Sample Location: TP204 - (0.3 - 0.4m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	16.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		No	
Liquid Limit (%)	AS 1289.3.1.1	68	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	19	
Plasticity Index (%)	AS 1289.3.3.1	49	

Comments

N/A

Report No: MAT:NEW17W-4926--S01

Issue No: 1

Material Test Report

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stages 6 & 9



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 9/11/2017

Sample Details

Sample ID: NEW17W-4926--S01
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 24/10/2017
Source: On-Site
Material: Sandy Clay
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP602 - (0.2 - 0.25m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	3.5	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	27	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	17	
Plasticity Index (%)	AS 1289.3.3.1	10	

Comments

N/A

Report No: MAT:NEW17W-4926--S05

Issue No: 1

Material Test Report

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stages 6 & 9



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 6/11/2017

Sample Details

Sample ID: NEW17W-4926--S05
Sampling Method: AS1289.1.2.1 cl 6.4b
Date Sampled: 24/10/2017
Source: On-Site
Material: Clayey Sand
Specification: No Specification
Project Location: Pitt Street, Teralba
Sample Location: TP903 - (0.1 - 0.2m)

Test Results

Description	Method	Result	Limits
Sample History	AS 1289.1.1	Air-dried	
Preparation	AS 1289.1.1	Dry Sieved	
Linear Shrinkage (%)	AS 1289.3.4.1	3.0	
Mould Length (mm)		250	
Crumbling		No	
Curling		No	
Cracking		Yes	
Liquid Limit (%)	AS 1289.3.1.1	23	
Method		Four Point	
Plastic Limit (%)	AS 1289.3.2.1	15	
Plasticity Index (%)	AS 1289.3.3.1	8	

Comments

N/A

Shrink Swell Index Report

Report No: SSI:NEW17W-3159--S05

Issue No: 2

This report replaces all previous issues of report no 'SSI:NEW17W-3159--S05'.

Client: McCloy Development Management Pty Ltd
Suite 1 Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 5



Accredited for compliance with ISO/IEC 17025 - Testing
The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

[Signature]

Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 11/08/2017

Sample Details

Sample ID: NEW17W-3159--S05

Test Request No.:

Material: Sandy Clay

Source: On-Site

Specification: No Specification

Project Location: Pitt Street, Teralba

Sample Location: TP5-5 - (0.4 - 0.8m)

Borehole Number: TP5-5

Borehole Depth (m): 0.4 - 0.8

Client Sample ID:

Sampling Method: AS1289.1.2.1 cl 6.5.4


Date Sampled: 28/07/2017

Date Submitted: 31/07/2017

Swell Test	AS 1289.7.1.1
Swell on Saturation (%):	-0.7
Moisture Content before (%):	15.2
Moisture Content after (%):	17.9
Est. Unc. Comp. Strength before (kPa):	>600
Est. Unc. Comp. Strength after (kPa):	550

Shrink Test	AS 1289.7.1.1
Shrink on drying (%):	1.6
Shrinkage Moisture Content (%):	15.4
Est. inert material (%):	15%
Crumbling during shrinkage:	Nil
Cracking during shrinkage:	Minor

Shrink Swell



Shrink Swell Index - Iss (%): 0.9

Comments

Report No: SSI:NEW16W-0030--S01

Issue No: 1

Shrink Swell Index Report

Client: McCloy Teralba Pty Ltd
Suite 1, Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 5 to 9



Accredited for compliance with ISO/IEC 17025
The results of the tests, calibrations and/or
measurements included in this document are traceable
to Australian/national standards

[Signature]

Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 22/01/2016

Sample Details

Sample ID: NEW16W-0030--S01

Client Sample ID: -

Test Request No.: -

Sampling Method: AS1289.1.2.1 cl 6.5

Material: CLAY

Date Sampled: 12/01/2016

Source: On-Site

Date Submitted: 14/01/2015

Specification: No Specification

Project Location: Pitt Street, Teralba

Sample Location: TP105 - 0.4 to 0.8m

Borehole Number: TP105

Borehole Depth (m): 0.4 to 0.8m

Swell Test

AS 1289.7.1.1


Swell on Saturation (%): 0.2
Moisture Content before (%): 17.6
Moisture Content after (%): 18.4
Est. Unc. Comp. Strength before (kPa): 500
Est. Unc. Comp. Strength after (kPa): 350

Shrink Test

AS 1289.7.1.1

Shrink on drying (%): 2.3
Shrinkage Moisture Content (%): 17.6
Est. inert material (%): 0
Crumbling during shrinkage: Nil
Cracking during shrinkage: Moderate

Shrink Swell



Shrink Swell Index - Iss (%): 1.3

Comments

Report No: SSI:NEW16W-0030--S03

Issue No: 1

Shrink Swell Index Report

Client: McCloy Teralba Pty Ltd
Suite 1, Level 3, 426 King Street
Newcastle West NSW 2300

Principal:

Project No.: NEW15P-0070A

Project Name: Proposed Subdivision - Billy's Lookout - Stage 5 to 9



Accredited for compliance with ISO/IEC 17025
The results of the tests, calibrations and/or
measurements included in this document are traceable
to Australian/national standards

Dane Cullen

Approved Signatory: Dane Cullen
(Senior Geotechnician)
NATA Accredited Laboratory Number: 18686
Date of Issue: 22/01/2016

Sample Details

Sample ID: NEW16W-0030--S03

Client Sample ID: -

Test Request No.: -

Sampling Method: AS1289.1.2.1 cl 6.5

Material: Sandy CLAY

Date Sampled: 12/01/2016

Source: On-Site

Date Submitted: 14/01/2015

Specification: No Specification

Project Location: Pitt Street, Teralba

Sample Location: TP112 - 0.3 to 0.55m

Borehole Number: TP112

Borehole Depth (m): 0.3 to 0.55m

Swell Test

AS 1289.7.1.1


Swell on Saturation (%): -1.0
Moisture Content before (%): 22.8
Moisture Content after (%): 29.0
Est. Unc. Comp. Strength before (kPa): 180
Est. Unc. Comp. Strength after (kPa): 190

Shrink Test

AS 1289.7.1.1

Shrink on drying (%): 1.9
Shrinkage Moisture Content (%): 22.4
Est. inert material (%): 0
Crumbling during shrinkage: Nil
Cracking during shrinkage: Minor

Shrink Swell



Shrink Swell Index - Iss (%): 1.1

Comments

APPENDIX C:

CSIRO Sheet BTF 18

**Foundation Maintenance and Footing
Performance: A Homeowner's Guide**

Foundation Maintenance and Footing Performance: A Homeowner's Guide



CSIRO

BTF 18
replaces
Information
Sheet 10/91

Buildings can and often do move. This movement can be up, down, lateral or rotational. The fundamental cause of movement in buildings can usually be related to one or more problems in the foundation soil. It is important for the homeowner to identify the soil type in order to ascertain the measures that should be put in place in order to ensure that problems in the foundation soil can be prevented, thus protecting against building movement.

This Building Technology File is designed to identify causes of soil-related building movement, and to suggest methods of prevention of resultant cracking in buildings.

Soil Types

The types of soils usually present under the topsoil in land zoned for residential buildings can be split into two approximate groups – granular and clay. Quite often, foundation soil is a mixture of both types. The general problems associated with soils having granular content are usually caused by erosion. Clay soils are subject to saturation and swell/shrink problems.

Classifications for a given area can generally be obtained by application to the local authority, but these are sometimes unreliable and if there is doubt, a geotechnical report should be commissioned. As most buildings suffering movement problems are founded on clay soils, there is an emphasis on classification of soils according to the amount of swell and shrinkage they experience with variations of water content. The table below is Table 2.1 from AS 2870, the Residential Slab and Footing Code.

Causes of Movement

Settlement due to construction

There are two types of settlement that occur as a result of construction:

- Immediate settlement occurs when a building is first placed on its foundation soil, as a result of compaction of the soil under the weight of the structure. The cohesive quality of clay soil mitigates against this, but granular (particularly sandy) soil is susceptible.
- Consolidation settlement is a feature of clay soil and may take place because of the expulsion of moisture from the soil or because of the soil's lack of resistance to local compressive or shear stresses. This will usually take place during the first few months after construction, but has been known to take many years in exceptional cases.

These problems are the province of the builder and should be taken into consideration as part of the preparation of the site for construction. Building Technology File 19 (BTF 19) deals with these problems.

Erosion

All soils are prone to erosion, but sandy soil is particularly susceptible to being washed away. Even clay with a sand component of say 10% or more can suffer from erosion.

Saturation

This is particularly a problem in clay soils. Saturation creates a bog-like suspension of the soil that causes it to lose virtually all of its bearing capacity. To a lesser degree, sand is affected by saturation because saturated sand may undergo a reduction in volume – particularly imported sand fill for bedding and blinding layers. However, this usually occurs as immediate settlement and should normally be the province of the builder.

Seasonal swelling and shrinkage of soil

All clays react to the presence of water by slowly absorbing it, making the soil increase in volume (see table below). The degree of increase varies considerably between different clays, as does the degree of decrease during the subsequent drying out caused by fair weather periods. Because of the low absorption and expulsion rate, this phenomenon will not usually be noticeable unless there are prolonged rainy or dry periods, usually of weeks or months, depending on the land and soil characteristics.

The swelling of soil creates an upward force on the footings of the building, and shrinkage creates subsidence that takes away the support needed by the footing to retain equilibrium.

Shear failure

This phenomenon occurs when the foundation soil does not have sufficient strength to support the weight of the footing. There are two major post-construction causes:

- Significant load increase.
- Reduction of lateral support of the soil under the footing due to erosion or excavation.
- In clay soil, shear failure can be caused by saturation of the soil adjacent to or under the footing.

GENERAL DEFINITIONS OF SITE CLASSES

Class	Foundation
A	Most sand and rock sites with little or no ground movement from moisture changes
S	Slightly reactive clay sites with only slight ground movement from moisture changes
M	Moderately reactive clay or silt sites, which can experience moderate ground movement from moisture changes
H	Highly reactive clay sites, which can experience high ground movement from moisture changes
E	Extremely reactive sites, which can experience extreme ground movement from moisture changes
A to P	Filled sites
P	Sites which include soft soils, such as soft clay or silt or loose sands; landslip; mine subsidence; collapsing soils; soils subject to erosion; reactive sites subject to abnormal moisture conditions or sites which cannot be classified otherwise

Tree root growth

Trees and shrubs that are allowed to grow in the vicinity of footings can cause foundation soil movement in two ways:

- Roots that grow under footings may increase in cross-sectional size, exerting upward pressure on footings.
- Roots in the vicinity of footings will absorb much of the moisture in the foundation soil, causing shrinkage or subsidence.

Unevenness of Movement

The types of ground movement described above usually occur unevenly throughout the building's foundation soil. Settlement due to construction tends to be uneven because of:

- Differing compaction of foundation soil prior to construction.
- Differing moisture content of foundation soil prior to construction.

Movement due to non-construction causes is usually more uneven still. Erosion can undermine a footing that traverses the flow or can create the conditions for shear failure by eroding soil adjacent to a footing that runs in the same direction as the flow.

Saturation of clay foundation soil may occur where subfloor walls create a dam that makes water pond. It can also occur wherever there is a source of water near footings in clay soil. This leads to a severe reduction in the strength of the soil which may create local shear failure.

Seasonal swelling and shrinkage of clay soil affects the perimeter of the building first, then gradually spreads to the interior. The swelling process will usually begin at the uphill extreme of the building, or on the weather side where the land is flat. Swelling gradually reaches the interior soil as absorption continues. Shrinkage usually begins where the sun's heat is greatest.

Effects of Uneven Soil Movement on Structures

Erosion and saturation

Erosion removes the support from under footings, tending to create subsidence of the part of the structure under which it occurs. Brickwork walls will resist the stress created by this removal of support by bridging the gap or cantilevering until the bricks or the mortar bedding fail. Older masonry has little resistance. Evidence of failure varies according to circumstances and symptoms may include:

- Step cracking in the mortar beds in the body of the wall or above/below openings such as doors or windows.
- Vertical cracking in the bricks (usually but not necessarily in line with the vertical beds or perpend).

Isolated piers affected by erosion or saturation of foundations will eventually lose contact with the bearers they support and may tilt or fall over. The floors that have lost this support will become bouncy, sometimes rattling ornaments etc.

Seasonal swelling/shrinkage in clay

Swelling foundation soil due to rainy periods first lifts the most exposed extremities of the footing system, then the remainder of the perimeter footings while gradually permeating inside the building footprint to lift internal footings. This swelling first tends to create a dish effect, because the external footings are pushed higher than the internal ones.

The first noticeable symptom may be that the floor appears slightly dished. This is often accompanied by some doors binding on the floor or the door head, together with some cracking of cornice mitres. In buildings with timber flooring supported by bearers and joists, the floor can be bouncy. Externally there may be visible dishing of the hip or ridge lines.

As the moisture absorption process completes its journey to the innermost areas of the building, the internal footings will rise. If the spread of moisture is roughly even, it may be that the symptoms will temporarily disappear, but it is more likely that swelling will be uneven, creating a difference rather than a disappearance in symptoms. In buildings with timber flooring supported by bearers and joists, the isolated piers will rise more easily than the strip footings or piers under walls, creating noticeable doming of flooring.

Trees can cause shrinkage and damage



As the weather pattern changes and the soil begins to dry out, the external footings will be first affected, beginning with the locations where the sun's effect is strongest. This has the effect of lowering the external footings. The doming is accentuated and cracking reduces or disappears where it occurred because of dishing, but other cracks open up. The roof lines may become convex.

Doming and dishing are also affected by weather in other ways. In areas where warm, wet summers and cooler dry winters prevail, water migration tends to be toward the interior and doming will be accentuated, whereas where summers are dry and winters are cold and wet, migration tends to be toward the exterior and the underlying propensity is toward dishing.

Movement caused by tree roots

In general, growing roots will exert an upward pressure on footings, whereas soil subject to drying because of tree or shrub roots will tend to remove support from under footings by inducing shrinkage.

Complications caused by the structure itself

Most forces that the soil causes to be exerted on structures are vertical – i.e. either up or down. However, because these forces are seldom spread evenly around the footings, and because the building resists uneven movement because of its rigidity, forces are exerted from one part of the building to another. The net result of all these forces is usually rotational. This resultant force often complicates the diagnosis because the visible symptoms do not simply reflect the original cause. A common symptom is binding of doors on the vertical member of the frame.

Effects on full masonry structures

Brickwork will resist cracking where it can. It will attempt to span areas that lose support because of subsided foundations or raised points. It is therefore usual to see cracking at weak points, such as openings for windows or doors.

In the event of construction settlement, cracking will usually remain unchanged after the process of settlement has ceased.

With local shear or erosion, cracking will usually continue to develop until the original cause has been remedied, or until the subsidence has completely neutralised the affected portion of footing and the structure has stabilised on other footings that remain effective.

In the case of swell/shrink effects, the brickwork will in some cases return to its original position after completion of a cycle, however it is more likely that the rotational effect will not be exactly reversed, and it is also usual that brickwork will settle in its new position and will resist the forces trying to return it to its original position. This means that in a case where swelling takes place after construction and cracking occurs, the cracking is likely to at least partly remain after the shrink segment of the cycle is complete. Thus, each time the cycle is repeated, the likelihood is that the cracking will become wider until the sections of brickwork become virtually independent.

With repeated cycles, once the cracking is established, if there is no other complication, it is normal for the incidence of cracking to stabilise, as the building has the articulation it needs to cope with the problem. This is by no means always the case, however, and monitoring of cracks in walls and floors should always be treated seriously.

Upheaval caused by growth of tree roots under footings is not a simple vertical shear stress. There is a tendency for the root to also exert lateral forces that attempt to separate sections of brickwork after initial cracking has occurred.

The normal structural arrangement is that the inner leaf of brickwork in the external walls and at least some of the internal walls (depending on the roof type) comprise the load-bearing structure on which any upper floors, ceilings and the roof are supported. In these cases, it is internally visible cracking that should be the main focus of attention, however there are a few examples of dwellings whose external leaf of masonry plays some supporting role, so this should be checked if there is any doubt. In any case, externally visible cracking is important as a guide to stresses on the structure generally, and it should also be remembered that the external walls must be capable of supporting themselves.

Effects on framed structures

Timber or steel framed buildings are less likely to exhibit cracking due to swell/shrink than masonry buildings because of their flexibility. Also, the doming/dishing effects tend to be lower because of the lighter weight of walls. The main risks to framed buildings are encountered because of the isolated pier footings used under walls. Where erosion or saturation cause a footing to fall away, this can double the span which a wall must bridge. This additional stress can create cracking in wall linings, particularly where there is a weak point in the structure caused by a door or window opening. It is, however, unlikely that framed structures will be so stressed as to suffer serious damage without first exhibiting some or all of the above symptoms for a considerable period. The same warning period should apply in the case of upheaval. It should be noted, however, that where framed buildings are supported by strip footings there is only one leaf of brickwork and therefore the externally visible walls are the supporting structure for the building. In this case, the subfloor masonry walls can be expected to behave as full brickwork walls.

Effects on brick veneer structures

Because the load-bearing structure of a brick veneer building is the frame that makes up the interior leaf of the external walls plus perhaps the internal walls, depending on the type of roof, the building can be expected to behave as a framed structure, except that the external masonry will behave in a similar way to the external leaf of a full masonry structure.

Water Service and Drainage

Where a water service pipe, a sewer or stormwater drainage pipe is in the vicinity of a building, a water leak can cause erosion, swelling or saturation of susceptible soil. Even a minuscule leak can be enough to saturate a clay foundation. A leaking tap near a building can have the same effect. In addition, trenches containing pipes can become watercourses even though backfilled, particularly where broken rubble is used as fill. Water that runs along these trenches can be responsible for serious erosion, interstrata seepage into subfloor areas and saturation.

Pipe leakage and trench water flows also encourage tree and shrub roots to the source of water, complicating and exacerbating the problem.

Poor roof plumbing can result in large volumes of rainwater being concentrated in a small area of soil:

- Incorrect falls in roof guttering may result in overflows, as may gutters blocked with leaves etc.

- Corroded guttering or downpipes can spill water to ground.
- Downpipes not positively connected to a proper stormwater collection system will direct a concentration of water to soil that is directly adjacent to footings, sometimes causing large-scale problems such as erosion, saturation and migration of water under the building.

Seriousness of Cracking

In general, most cracking found in masonry walls is a cosmetic nuisance only and can be kept in repair or even ignored. The table below is a reproduction of Table C1 of AS 2870.

AS 2870 also publishes figures relating to cracking in concrete floors, however because wall cracking will usually reach the critical point significantly earlier than cracking in slabs, this table is not reproduced here.

Prevention/Cure

Plumbing

Where building movement is caused by water service, roof plumbing, sewer or stormwater failure, the remedy is to repair the problem. It is prudent, however, to consider also rerouting pipes away from the building where possible, and relocating taps to positions where any leakage will not direct water to the building vicinity. Even where gully traps are present, there is sometimes sufficient spill to create erosion or saturation, particularly in modern installations using smaller diameter PVC fixtures. Indeed, some gully traps are not situated directly under the taps that are installed to charge them, with the result that water from the tap may enter the backfilled trench that houses the sewer piping. If the trench has been poorly backfilled, the water will either pond or flow along the bottom of the trench. As these trenches usually run alongside the footings and can be at a similar depth, it is not hard to see how any water that is thus directed into a trench can easily affect the foundation's ability to support footings or even gain entry to the subfloor area.

Ground drainage

In all soils there is the capacity for water to travel on the surface and below it. Surface water flows can be established by inspection during and after heavy or prolonged rain. If necessary, a grated drain system connected to the stormwater collection system is usually an easy solution.

It is, however, sometimes necessary when attempting to prevent water migration that testing be carried out to establish watertable height and subsoil water flows. This subject is referred to in BTF 19 and may properly be regarded as an area for an expert consultant.

Protection of the building perimeter

It is essential to remember that the soil that affects footings extends well beyond the actual building line. Watering of garden plants, shrubs and trees causes some of the most serious water problems.

For this reason, particularly where problems exist or are likely to occur, it is recommended that an apron of paving be installed around as much of the building perimeter as necessary. This paving

CLASSIFICATION OF DAMAGE WITH REFERENCE TO WALLS		
Description of typical damage and required repair	Approximate crack width limit (see Note 3)	Damage category
Hairline cracks	<0.1 mm	0
Fine cracks which do not need repair	<1 mm	1
Cracks noticeable but easily filled. Doors and windows stick slightly	<5 mm	2
Cracks can be repaired and possibly a small amount of wall will need to be replaced. Doors and windows stick. Service pipes can fracture. Weathertightness often impaired	5–15 mm (or a number of cracks 3 mm or more in one group)	3
Extensive repair work involving breaking-out and replacing sections of walls, especially over doors and windows. Window and door frames distort. Walls lean or bulge noticeably, some loss of bearing in beams. Service pipes disrupted	15–25 mm but also depend on number of cracks	4



- Water that is transmitted into masonry, metal or timber building elements causes damage and/or decay to those elements.
- High subfloor humidity and moisture content create an ideal environment for various pests, including termites and spiders.
- Where high moisture levels are transmitted to the flooring and walls, an increase in the dust mite count can ensue within the living areas. Dust mites, as well as dampness in general, can be a health hazard to inhabitants, particularly those who are abnormally susceptible to respiratory ailments.

The garden

The ideal vegetation layout is to have lawn or plants that require only light watering immediately adjacent to the drainage or paving edge, then more demanding plants, shrubs and trees spread out in that order.

Overwatering due to misuse of automatic watering systems is a common cause of saturation and water migration under footings. If it is necessary to use these systems, it is important to remove garden beds to a completely safe distance from buildings.

Existing trees

Where a tree is causing a problem of soil drying or there is the existence or threat of upheaval of footings, if the offending roots are subsidiary and their removal will not significantly damage the tree, they should be severed and a concrete or metal barrier placed vertically in the soil to prevent future root growth in the direction of the building. If it is not possible to remove the relevant roots without damage to the tree, an application to remove the tree should be made to the local authority. A prudent plan is to transplant likely offenders before they become a problem.

Information on trees, plants and shrubs

State departments overseeing agriculture can give information regarding root patterns, volume of water needed and safe distance from buildings of most species. Botanic gardens are also sources of information. For information on plant roots and drains, see Building Technology File 17.

Excavation

Excavation around footings must be properly engineered. Soil supporting footings can only be safely excavated at an angle that allows the soil under the footing to remain stable. This angle is called the angle of repose (or friction) and varies significantly between soil types and conditions. Removal of soil within the angle of repose will cause subsidence.

Remediation

Where erosion has occurred that has washed away soil adjacent to footings, soil of the same classification should be introduced and compacted to the same density. Where footings have been undermined, augmentation or other specialist work may be required. Remediation of footings and foundations is generally the realm of a specialist consultant.

Where isolated footings rise and fall because of swell/shrink effect, the homeowner may be tempted to alleviate floor bounce by filling the gap that has appeared between the bearer and the pier with blocking. The danger here is that when the next swell segment of the cycle occurs, the extra blocking will push the floor up into an accentuated dome and may also cause local shear failure in the soil. If it is necessary to use blocking, it should be by a pair of fine wedges and monitoring should be carried out fortnightly.

This BTF was prepared by John Lewer FAIB, MIAMA, Partner, Construction Diagnosis.

should extend outwards a minimum of 900 mm (more in highly reactive soil) and should have a minimum fall away from the building of 1:60. The finished paving should be no less than 100 mm below brick vent bases.

It is prudent to relocate drainage pipes away from this paving, if possible, to avoid complications from future leakage. If this is not practical, earthenware pipes should be replaced by PVC and backfilling should be of the same soil type as the surrounding soil and compacted to the same density.

Except in areas where freezing of water is an issue, it is wise to remove taps in the building area and relocate them well away from the building – preferably not uphill from it (see BTF 19).

It may be desirable to install a grated drain at the outside edge of the paving on the uphill side of the building. If subsoil drainage is needed this can be installed under the surface drain.

Condensation

In buildings with a subfloor void such as where bearers and joists support flooring, insufficient ventilation creates ideal conditions for condensation, particularly where there is little clearance between the floor and the ground. Condensation adds to the moisture already present in the subfloor and significantly slows the process of drying out. Installation of an adequate subfloor ventilation system, either natural or mechanical, is desirable.

Warning: Although this Building Technology File deals with cracking in buildings, it should be said that subfloor moisture can result in the development of other problems, notably:

The information in this and other issues in the series was derived from various sources and was believed to be correct when published.

The information is advisory. It is provided in good faith and not claimed to be an exhaustive treatment of the relevant subject.

Further professional advice needs to be obtained before taking any action based on the information provided.

Distributed by

CSIRO PUBLISHING PO Box 1139, Collingwood 3066, Australia

Freecall 1800 645 051 Tel (03) 9662 7666 Fax (03) 9662 7555 www.publish.csiro.au

Email: publishing.sales@csiro.au

© CSIRO 2003. Unauthorised copying of this Building Technology file is prohibited